

(ii) *One amber reflector at or near the front of the load; and*

(iii) *On the rearmost support for the load, one combination marker lamp showing amber to the front and red to the rear and side, mounted to indicate maximum width of the pole trailer.*

(b) *Whenever identification lamps are required or permitted by this subtitle, they shall be grouped in a horizontal row, with lamp centers spaced not less than 6 nor more than 12 inches apart, and mounted on the permanent structure of the vehicle as close as practicable to the vertical centerline; provided, however, that where the cab of a vehicle is not more than 42 inches wide at the front roof line, a single identification lamp at the center of the cab shall be deemed to comply with the requirements for front identification lamps.*

§ 12-209. *Color of clearance lamps, identification lamps, side marker lamps, back-up lamps and reflectors.*

(a) *Front clearance lamps, identification lamps and those marker lamps and reflectors mounted on the front or on the side near the front of a vehicle shall display or reflect an amber color.*

(b) *Rear clearance lamps, identification lamps, and those marker lamps and reflectors mounted on the rear or on the sides near the rear of a vehicle shall display or reflect a red color.*

§ 12-210. *Mounting of reflectors, clearance lamps and side marker lamps.*

(a) *Reflectors when required by section 12-208 shall be mounted at a height not less than 24 inches and not higher than 60 inches above the ground on which the vehicle stands, except that if the highest part of the permanent structure of the vehicle is less than 24 inches the reflector at that point shall be mounted as high as that part of the permanent structure will permit.*

(b) *The rear reflectors on a pole trailer may be mounted on each side of the bolster or load.*

(c) *Any required red reflector on the rear of a vehicle may be incorporated with the tail lamp, but the reflector shall meet all the other reflector requirements of this subtitle.*

(d) *Clearance lamps shall be mounted on the permanent structure of the vehicle in a manner to indicate its extreme width and as near the top thereof as practicable. Clearance lamps and side marker lamps may be mounted in combination provided illumination is given as required herein with reference to both.*

§ 12-211. *Visibility requirements for reflectors, clearance lamps, identification lamps, and marker lamps.*

(a) *Every reflector upon any vehicle referred to in section 12-208 shall be of such size and characteristics and maintained to be readily visible at nighttime from all distances within 600 feet to 100 feet from the vehicle when directly in front of lawful upper beams of head lamps. Reflectors required to be mounted on the sides of the vehicle shall reflect the required color of light to the sides, and those mounted on the rear shall reflect a red color to the rear.*