MINERAL RESOURCES AND MINED LAND INVENTORY, PRINCE GEORGE'S COUNTY, MARYLAND

By

Karen R. Kuff

1980

STATE OF MARYLAND
DEPARTMENT OF NATURAL RESOURCES
MARYLAND GEOLOGICAL SURVEY
Kenneth N. Weaver, Director

INTRODUCTION

This map is an inventory of past and present mineral operations and potential mineral resources in Prince George's County. The resources extracted today are primarily sand and gravel, the rest being construction sand, clay and fill material. Historically, iron ore, ocher (paint ore), marl and molding sands were mined in the County. Prince George's County has been the leading producer of sand and gravel in Maryland for over ten years. The following graph shows the value of mineral production in the County from 1960 to 1976:



Prince George's County Mineral Production
(from U.S. Bureau of Mines, Mineral Industry of Maryland, 1960-1976)

At present, there are thirty active pits in the County and twelve working plants or storage areas located on sites of former operations. The DESCRIPTION OF OPERATIONS below lists each active operation and includes the mineral producer's name (where known), operational status, and a location number keyed to the map. In all, over 8,700 acres have been disturbed by the mining industry and the products used for commercial, industrial, residential and governmental purposes. Approximately 14.2% of this area is currently being worked or utilized for plant and storage sites. About 47.3% of the disturbed land has been reclaimed to a condition suitable for farming, forestry, recreation, planned, developed, or otherwise utilized. The remaining 38.7% represents acreage that has not been reclaimed and is not currently being worked. However, these figures do not reflect the acreage involved in numerous small mineral operations whose dimensions and exact locations have been obliterated through time. The following chart gives a status report on disturbed land:

Inactive and Abandoned Acreage	*Reclaimed Acreage*	*Working Acreage*	*Total Acreage*
3,370.5	4,106.4	1,239.4	8,716.3

The information presented here was compiled from the literature and field investigations (1975-1979). Aerial photographs were used from the following sources: Soil Conservation Service, U.S. Department of Agriculture, 1:20,000 (Photographs (1938, 1952, 1963, 1970); Photo Service, Inc., (1972); and LANDSAT-1 aircraft support photography (1974)).

Special thanks are given to Dr. John D. Glaser of the Maryland Geological Survey for information and assistance provided, and to Timothy J. Schmidt and Anne R. Newman for their help in the field.

PRESENT AND POTENTIAL RESOURCES

The term "potential resources" is used here to indicate those deposits that have been worked or are currently being worked in the County and are therefore a proven economic resource. While some of the resources mentioned below are not currently being worked, they have been in the past and the quantity, quality, chemical and physical nature of these deposits justify their consideration here as a viable economic resource for the future. For the locale and general description of units discussed but not shown on the map, please refer to the DESCRIPTION OF GENERAL GEOLOGY.

Sand and Gravel: Extensive deposits of sand and gravel suitable for use in the construction industry are found in portions of three geologic units in Prince George's County: (1) Potomac Group sand-gravel facies; (2) Upland Gravels, and (3) in the upstream Terrace Deposits along the Patuxent River. The sand-gravel facies of the Potomac Group is composed of interbedded layers of gravel, sand, silt and clay. Sand and gravel is the dominant lithology in the northwestern portion of the County. The percentage of gravel ranges from 20 to 70% with an average of 45%; sand ranges from 30 to 80% with an average of 55%. Clay varies from 0% to 33% but averages 12%. This portion of the Potomac Group has been worked for many years; currently, there are seven active operations in this unit.

The Upland Gravels are the primary source of sand and gravel in Prince George's County and there are 20 active pits in this unit. In undisturbed areas, the sand-gravel portion of the unit is overlain by as much as 15 feet of sandy loam. Screen analyses of the Upland Gravels from operations throughout the central County of 63.4% gravel, 33.3% sand, and 3.3% of silt and clay. The percentage of gravel present decreases southeastward from Washington, D.C.

Although there are no current operations in the northern Patuxent River Terrace Deposits, sand and gravel was once actively mined from the bed in Prince George's County. In some areas, these deposits are 100% sand (with no appreciable amount of sand and gravel); however, the Terrace Deposits along the Patuxent River in Prince George's County tend to be thinner and more variable in composition with less gravel, particularly toward the south. Another source of sand and gravel (not shown on the map) was dredging the banks, tidal flats, and beds of the Potomac River and the mouths of confluent streams, Indian Creek, and the Patuxent River near Bowie. At one time, these areas provided the greatest production of sand and gravel in the County. The earliest recorded operation was begun in 1899.

Discontinuous Sand and Gravel, Sand: Those deposits consisting primarily of sand interbedded with gravel, silt, and some clay of variable thickness are included in this category. The probability of finding commercially valuable sand and gravel in this unit is not as high as in the preceding group. These deposits include: (1) portions of the sand-gravel facies of the Potomac Group which are not adjacent to major streams such as the Patuxent River and adjacent to major creeks in the County. The southeastern portion of the sand-gravel facies of the Potomac Group consists primarily of quartz sand with variable amounts of gravel, silt, and clay with iron concretions. This unit has been mined for sand and gravel in some areas, and there is currently one active operation in these materials. Sand and gravel occurs in some places in the Terrace Deposits. The deposits are primarily sand, clayey sand, and pebbly sand with greater percentages of silt and clay than the Upland Deposits. Sand and gravel beds in these Terrace Deposits is variable, as is the amount of silt present. Although there are no current operations in these deposits, they have been worked in the past and economically exploitable sand and gravel may remain. Another source of sand not shown on the map is the alluvial deposits. In 1903, large sand pits were developed east of Laurel in the alluvial deposits along the Patuxent River. The sand was used for making filter beds for the District of Columbia's water system. It also was used to build the artificial hill under Union Station.

Clays: Two sources of clay in the County are the silt-clay facies of the Potomac Group and the Marlboro Clay. Clays in the Potomac Group are commonly found in beds ranging from 5 feet to 100 feet or more. Currently, there is one active clay operation in the Potomac Group. The Marlboro Clay was extensively worked near Upper Marlboro. Both clays are suitable for brick and other structural clay products. In the past, these clays were used for common pottery, smoking pipes, tiles and bricks. Formerly, clay for bricks was dug extensively near Washington from the surficial loam present in some Terrace Deposits. This loam is of considerable areal extent but is only 3 to 4 feet thick.

Diatomite: Diatomite or diatomaceous silt is present in the lower Calvert Formation. The map pattern shown indicates deposits in outcrop or with minimum overburden. The diatomite ranges from 4 to 17 feet thick, thickening from north to south. It varies in purity from about 20% to a maximum of 65% diatoms. A chemical analysis of the diatomite three miles southwest of Upper Marlboro (Glaser, 1971) shows:

SiO_2	81.2%
Al_2O_3	3.7%
Fe_2O_3	2.5%
CaO	0.9%
MgO	0.4%
K_2O	0.9%
Na_2O	0.2%
TiO_2	0.7%
Ignition Loss	6.4%
	96.9%

Although diatomite has not yet been exploited in the County, it offers a potential source of material for filtration media, abrasives, insulation, absorbant, or filler material.

Other Potential Resources: Other resources in the County of potential use only with changes in either the economic situation or technology are glauconite and phosphorite. Glauconite is found in the greensand of the Aquia and Nanjemoy Formations. It makes up from 5% to 60% of the sediment with the greatest percentage occurring in the Nanjemoy Formation. It has been used primarily for soil conditioning, and secondarily as a water softener. Phosphorite or phosphate is found in the basal portion of the Calvert Formation, with proportions ranging from trace amounts to 10% in the Aquia Formation. In the Aquia, the content of the phosphate pebbles varies from 15% to 25%. Its potential use is the fertilizer industry. For more information on these resources, see Glaser, 1971.

HISTORICAL MINERAL RESOURCES

Historical resources are those deposits that were worked in the past for minerals, but which are no longer of commercial value due to changes in technology and demand. For the location and general description of geologic units discussed but not shown on the map, please refer to DESCRIPTION OF GENERAL GEOLOGY.

Iron Ore: Early in the 19th Century, iron ore was one of the County's most important mineral resources. The iron ore used was primarily siderite and secondarily limonite. The ore occurs as concretions and lenticular bodies of limited extent, primarily within the silt-clay facies of the Potomac Group. It is also found in the Aquia Formation. The largest operation was known as the "Swampoodle Ore Banks" now the site of the U.S. Department of Agriculture Research Center in Beltsville. The pit was three quarters of a mile long and one quarter of a mile wide. In 1817, Muirkirk Furnace was established near Muirkirk and operated continuously until about 1916. The product was claimed by the proprietors to be the strongest pig iron produced in the United States. It was used for special items requiring great strength, i.e. cannons, car wheels, cylinders, and special kinds of steel.

Paint Ore: In the Potomac Group are clays rich in iron oxide which were excavated for paint pigments. Near Ft. Washington, this ore was mined during Colonial times as a "hole" dye for fabrics.

Building Stone: Four types of building stone have been used for local construction needs in the County. The granitic gneiss found in the Piedmont in the northwestern part of the County furnished material for foundations, rough stone work, and rustic flagging. In the Coastal Plain, indurated concretions and indurated beds that have been used for building purposes. One such is a tough white opal-cemented quartzite which occurs as large blocks scattered over the surface of the Upper Potomac Group. This material was quarried north of Collington. Another is a brown ferruginous conglomerate also present in the Potomac Group. This stone, which tends to weather to a brownish-orange color, was used primarily for foundations. Consolidated shelly sandstone present in the Aquia Formation have also been used for rough construction work.

Molding Sands: South of Upper Marlboro near the Conrail tracks is the only site in the County operated strictly for molding sands. Here a minor terrace deposit was worked by the Plum Point Molding Sand Company on Wilson's farm. Molding sands are used to cast metal.

Marl: In the Aquia Formation near Seat Pleasant there was at one time a "green-sand marl" operation. The fossil shells in the unit provided the necessary calcium carbonate, and with the presence of potassium from the glauconite and trace mineral phosphates, this unit provided an excellent local source of fertilizer.

DESCRIPTION OF GENERAL GEOLOGY

The geology of Prince George's County is predominantly comprised of layered unconsolidated Coastal Plain sediments. Crystalline rock outcrops is found only along incised streams near the Montgomery County boundary. The following legend briefly describes the nature of the various geologic units within the County shown on the small generalized geologic map. Those units of present or potential value as a mineral resource are shown on the large map. A more detailed description of the geology of Prince George's County is in preparation. For additional information on the geology of the County, refer to Cooke and Cloos (1951), Darton (1939), Glaser and Kuff (1978), Glaser (1973 and 1971), Hack (1977 and 1965), Keith, Miller and Bibbons (1911) and Wittington and Froelich (1974).

GENERAL GEOLOGIC MAP



GEOLOGIC LEGEND*



Alluvium, *sand, silt, clay, and gravel; interbedded, lenticular, poorly sorted, locally organic rich; yellow, gray, brown to grey. Found in stream channel areas. Gravel more common in upstream areas. Thickness variable, from a few feet unmodified or over-simplified. Thickness 1 to 15 feet.*

Terrace Deposits *sand, silt, variable amounts of gravel, clay; yellow, brown, grey; poorly sorted, relatively heterogeneous; locally organic rich; includes some thin, dark grey, clayey silt or muddy beds. Found adjacent to rivers and streams. In some areas, gravel is more common in upstream terraces. Thickness varies but is generally thinner on slopes. Thickness reaching a maximum of 40 feet.*

Upland Deposits *interbedded sand, silt, clay, and gravel; variable amounts of each; includes some lenticular beds. Color tan to orange, mottled green. Color due to iron oxide coatings on quartz grains. Gravel portion ranges from 0% to 70% and averages 45%. Sand ranges from 30% to 80% and averages 55%. Clay ranges from 0% to 33% and averages 12%. Thickness of unit variable, but is generally thinner on slopes.*

Calvert Formation *fine grained sand, silt, diatomaceous silt, and minor clay. Color light grey, olive grey, brown. Locally some beds abundantly fossiliferous. Lower part of unit contains diatomite in beds as much as 17 feet thick. Overlying basal coarse sand, gravel, and cobble conglomerate. Lower part of diatomaceous silt from 4 to 17 feet thick. Upper beds mostly fine sand and silt. Total thickness from 0 to 125 feet.*

Nanjemoy Formation *sand, variably glauconitic, locally clayey, locally very silty, poorly sorted, massively bedded sand, fine to medium grained, contains local lenses of fossiliferous clay. Color greenish grey to buff where known. Thickness as much as 100 feet.*

Marlboro Clay *lenticular clay, brittle when dry, blocky fracture, locally laminated, with minor silt partings and lenses. Color dark grey, mottled red and brown, locally red to reddish brown in middle. Outcrops mostly on slopes in southeastern portion of County. Thickness known to 35 feet, but probably greater. Thickness to 35 feet maximum.*

Aquia Formation *sand, variably clay, cobble and clayey, and calcareous sand with scars of fossils in sand, locally with calcareous sandstone up to 1 foot thick. Color green, grey, brown, weathering to rusty brown where exposed. Locally fossiliferous. Thickness to 50 feet. Basal limonite sandstone boulders common in east coast. Thickness 2 to 50 feet.*

Brightseat and Severn Formations *sand, variably clayey, micaceous, locally glauconitic. Generally fine to well sorted, locally fossiliferous. Color dark grey to black, weathering to dark brown. Thickness ranges from 0 to 40 feet.*

Potomac Group *divided into sand-gravel facies, silt-clay facies, and both facies undifferentiated in this report. This group has also been separated into the Arundel and Patapsco Formations elsewhere.*

Sand-Gravel Facies: *sand, pebbly sand, and gravel, with variable amounts of silt and clay with some beds of clay; poorly to well sorted, fine to coarse grained, poorly to well bedded. Color white, grey, brown, known to reproduced. Ferruginous iron oxide concretions and ferruginous sandstone ledges common. Gravel predominant in some areas, minor constituent in others. Thickness 0 to 200 feet.*

Silt-Clay Facies: *silt and clay with subordinate amounts of sand, generally massive and thin bedded. Color grey to dark grey, mottled red, brown and yellow locally. Thickness 0 to 100 feet.*

Undifferentiated Crystalline Rocks *Metamorphic rocks of the Piedmont Province. Outcrops only in northwestern portion of County.*

* modified from Glaser (1973) and Hack (1977).



REFERENCES

COOKE, C.W. and CLOOS, E., 1951, Geologic map of Prince Georgia and the District of Columbia: Md. Dept. of Geol., Mines and Water Resources. scale 1:62,500.

DARTON, N.H., 1939, The Marlboro clay: Econ. Geol., v. 43, p. 184-189.

_____, 1948, Gravel and sand deposits of eastern Maryland: U.S. Geol. Survey Bull. 950-A, 42 p.

DUNN, J.R., 1975, Construction materials, aggregates - sand and gravel: in Industrial Minerals and Rocks, A.I.M.E., p. 97-106.

GLASER, J.D., 1971, Geology and mineral resources of Southern Maryland: Md. Geol. Survey, Rept. of Inv. 15, 85 p.

_____, 1973, Mineral resources: *in* Bowie Quadrangle, Geologic and Environmental Atlas: Md. Geol. Survey, map 2, scale 1:24,000.

GLASER, J.D. and KUFF, K.R., 1978, Mount Vernon and Piscataway Quadrangles, Geologic and Environmental Atlas: Md. Geol. Survey, Q.A. 3, 3 maps, scale 1:24,000.

GOLDMAN, H.B. and RENING, D., 1975, Sand and gravel: *in* Industrials and Rocks, A.I.M.E., p. 1027-1043.

HACK, J.T., 1955, Geology of the Brandywine area and origin of the upland of Southern Maryland: U.S. Geol. Survey, Prof. Paper 267-A, 43 p.

_____, 1976, Map of mineral resources, Prince George's County, Maryland: U.S. Geol. Survey, Misc. Field Studies Map MF-768-A, scale 1:62,500.

_____, 1977, Geologic map for land-use planning, Prince George's County, Maryland: U.S. Geol. Survey, Misc. Inv. Series Map I-1064, scale 1:62,500.

HOPKINS, G.M., 1878, Atlas of Prince George's County, Maryland, from actual Steam Lithographic Press, reprint 1975, Prince George's County Hist. Soc., Riverdale, Md.

JENSEN, D.R., 1967, Selecting land use for sand and gravel sites: Nat. Sand and Gravel Assoc., 65 p.

THE JOHNS HOPKINS UNIVERSITY
MAR 17 1995
MAP COLLECTION

DESCRIPTION OF OPERATIONS

1 Contee Sand and Gravel Co., Inc.; working, part of landfill operation in north
2 Contee Sand and Gravel Co., Inc.; supply storage area
3 Contee Sand and Gravel Co., Inc.; supply storage area
4 Contee Sand and Gravel Co., Inc.; plant and storage area, sand and gravel or overgrown; east of 180, some areas being worked
5 Contee Sand and Gravel Co., Inc.; working, portions graded
6 A.H. Smith; working
7 Contee Sand and Gravel Co., Inc.; working, portion reclaimed
8 Cherry Hill Sand and Gravel Co., Inc.; reclamation in progress
9 Maryland Clay Products, Inc., working, portions graded and overgrown
10 Willard Sand and Gravel Company; intermittently working
11 Ammendale Sand and Gravel, Inc.; working
12 A.H. Smith; plant and storage site
13 Daisey Brothers, Inc.; intermittently working
14 A.H. Smith; plant and storage site
15 Arundel Asphalt Co. and Brandywine Sand and Gravel Co.; plant and storage site
16 Hi-Mar Corp.; intermittently working, primarily overgrown, school built on southern portion
17 Silver Hill Sand and Gravel Co.; plant and storage site
18 Buffalo Sand and Gravel Co.; plant and storage site
19 Inland Materials, Inc.; plant and storage site, southern portion being developed
20 Lone Star Industries, Inc.; plant and storage site
21 A.H. Smith; plant and storage site
22 Western Shore Mining Co.; working
23 Inland Materials, Inc.; working, portions reclaimed
24 Accokeek Mining Co., working
25 A.H. Smith; intermittently working
26 Prince George's Bank Run Gravel Corp.; working
27 Lone Star Industries, Inc.; intermittently working
28 Brandywine Sand and Gravel Co.; working
29 Brandywine Mining Co.; working
30 Brandywine Sand and Gravel Co., intermittently working
31 A.H. Smith; intermittently working
32 Western Shore Mining Co.; working
33 Brandywine Mining Co.; reclamation in progress
34 Lone Star Industries, Inc.; intermittently working, currently reclaiming pit to west
35 Brandywine Sand and Gravel Co.; working, filling in east side of operation
36 A.H. Smith; intermittently working
37 R.L. Gardner; presently reclaimed
38 R.L. Gardner, working
39 Daisey Brothers, Inc.; working
40 Inland Materials, Inc.; working
41 Sleepy Hollow, Inc.; working

EXPLANATION

- Sand and Gravel
- Discontinuous Sand and Gravel, Sand
- Potomac Group Clay
- Marlboro Clay
- Diatomite
- Boundary of Federal property excluded from this report
- ●1 Working operation, see DESCRIPTION OF OPERATIONS
- ■2 Plant and storage area, former working site, see DESCRIPTION OF OPERATIONS
- ▲ Reclaimed extraction site
- Abandoned or inactive sand and gravel, clay, sand, ocher or marl operation
- Site of former iron ore operation
- Borrow pit
- Boundary of larger operation



Base Map, Prince George's County Topographic Map published by Maryland Geological Survey

Copies of Map available from
Maryland Geological Survey
Johns Hopkins University
Baltimore, Maryland 21218

Williams & Heintz Map Corporation, Washington, D.C. 20027