

and of sufficient illuminating power to be visible at a distance of two hundred (200) feet in the direction in which displayed, and to reveal any person, vehicle or substantial object ten feet to both sides of any such vehicle, at a point ten feet ahead of the lamps, except when at rest it shall display at least one light, showing white to the front and red to the rear, carried to the left of the motor vehicles, visible from both front and rear for a distance of not less than two hundred feet. Said motor vehicle when in use shall also display on the rear a lamp so constructed and placed as to show a red light from the rear and throw a white light directly upon the rear registration marker and render the numerals thereon visible for at least 25 feet in the direction from which the vehicle is proceeding. A motor-cycle, whether in use or at rest, shall display on the forward-part one white or tinted light as aforesaid and a red light to the rear so constructed and placed as to throw a white light directly upon the registration marker as prescribed in the case of any other motor vehicle; provided, however, that the operator of such motor vehicle may proceed to his destination in the event of a bona fide failure of one or more of his lights to operate if he sound his bell or other signalling device at least once in every two hundred (200) feet, does not proceed at a rate of speed greater than one mile in six minutes, and takes the first reasonable opportunity to put his lights in order, otherwise to be deemed guilty of a violation of the foregoing provision. The above provisions as to rear lights shall also apply to vehicles which are trailed or towed by motor vehicles.

It shall be unlawful to use on a vehicle of any kind operated on the public highways of this State, including motor-cycles, any lighting device of over four candle power equipped with a reflector unless the same shall be so designed, deflected or arranged that no portion of the beam of reflected light projected to the left of the axis of the vehicle when measured seventy-five (75) feet or more ahead of the lamps shall rise above forty-two (42) inches from the level surface on which the vehicle stands under all conditions of load. If, in addition to headlights, any such vehicle is equipped with any auxiliary light, projecting device or devices, other than the rear lamp,