- SEC. 70. Such miner shall immediately cease work if at any time he finds his place has become dangerous from any cause or condition beyond his power to remedy. Upon leaving such place, he shall place some plain danger signal at the entrance thereto, to warn other persons from entering; and shall immediately notify the mine foreman; and he shall not return thereto until notified by the mine foreman that the danger has been removed.
- SEC. 71. It shall be the duty of each employee at any such mine to notify the mine foreman or other official of any unsafe condition, including unsafe conditions of any working place, haulage road, or traveling way, or of damage to doors, brattices, or of obstructions to any air passage or failure in the ventilation which may become known to such employee.
- SEC. 72. Any person who shall intentionally or carelessly injure any safety lamp, instrument, air course or brattice, or without authority handle, remove or damage any fencing, means of signalling, apparatus or machinery, or shall obstruct or throw open airways, or enter a place in or about any mine against caution, or carry fire, open lights, matches, pipes or other smokers' articles beyond any station beyond which approved safety lamps are used, or open any door the opening of which is forbidden, or disobey any order given in carrying out the provisions of this Act or regulation pursuant thereto, or do any other act whatsoever, whereby the lives or health of persons employed or the security of the mine property is endangered, shall be deemed guilty of a misdemeanor.
- SEC. 73. Such special duties relating to security of lives or property may be defined and required of each employee in or about such mines by classes of employment, as the Bureau by regulation may prescribe.
- SEC. 74. Each workman, when employed, shall have his attention directed to the general and special rules by the person employing him.

CHAPTER X—Mine Excavations.

SEC. 75. The operator of any such mine shall direct and see that proper breaks-through, for purposes of ventilation, are made between entries or in room pillars, at such distances apart, not more than thirty-five (35) yards nor less