

teriors are illuminated, shall display lighted lamps at the times mentioned in Section 213 when and as required in this section, except that such lamps may be but are not required to be lighted when any such vehicle is upon a highway which is sufficiently illuminated by street lamps to render any person or vehicle visible at a distance of 300 feet.

(b) Clearance Lamps. Every vehicle having a width at any part in excess of 80 inches shall be equipped with two clearance lamps located at the front and rear of such vehicle, two located at the front and displaying an amber light visible from a distance of 300 feet to the front of the vehicle and two located at the rear of the vehicle and displaying a red light visible from a distance of 300 feet to the rear of the vehicle, which said rear clearance lamps shall be in addition to the red rear lamp hereinbefore required, provided, however, that vehicles equipped with acetylene headlamps may be equipped, in lieu of such clearance lights, with an amber reflector in front and a red reflector in the rear, which shall be so designed and maintained to meet the requirements as to reflectors of this Article.

(c) Side-marker Lamps. Every vehicle or combination of such vehicles which exceeds 20 feet in overall length shall be equipped with at least 4 side marker lamps, 1 on each side near the front and 1 on each side near the rear. Said lamps shall display amber lights on each side near the front and red lights on each side near the rear, each one of the said four lights to be visible from a distance of 300 feet to the side of the vehicle on which it is located. In lieu of such side marker lamps any such vehicle may be equipped with four reflectors, one on each side near the front and one on each side near the rear. Two reflectors nearest the front shall be amber reflectors and the two reflectors nearest the rear shall be red reflectors, provided such marker lamps otherwise meet the requirements of this Article.

(d) Side-marker Lamps May Be Combined With Clearance Lamps. Side-marker lamps may be in combination with clearance lamps and may use the same light source.

217. LAMP OR FLAG ON PROJECTING LOAD. Whenever the load upon any vehicle extends to the rear 4 feet or more beyond the bed or body of such vehicle there shall be displayed at the extreme rear end of the load, at the times specified in Section 213 hereof, a red light or lantern plainly visible from a distance of at least 300 feet to the sides and rear. The red light or lantern required under this section shall be in addition to the red rear light required upon every vehicle. At