

faucets shall be located on each trailer coach space. An adequate supply of hot water shall be provided at all times in the service buildings for bathing, washing and laundry facilities.

1341 (1222H). (Sanitation Facilities.) Each park shall be provided with toilets, baths or showers, slop sinks and other sanitation facilities which shall conform to the following requirements:

(a) Toilet facilities for men and women shall be either in separate buildings at least 20 feet apart or shall be separated, if in the same building, by a sound-proof wall.

(b) Toilet facilities for women shall consist of not less than one flush toilet for every 10 trailer coach spaces, one shower or bath tub for every 10 trailer coach spaces and one lavatory for every 20 trailer coach spaces. Each toilet, shower and bath tub shall be in a private compartment.

(c) Toilet facilities for men shall consist of not less than one flush toilet for every 15 trailer coach spaces, one shower or bathtub for every 10 trailer coach spaces, one lavatory for every 10 trailer coach spaces and one urinal for every 15 trailer coach spaces. Each toilet, shower and bath tub shall be in a private compartment.

(d) Service buildings housing the toilet facilities shall be permanent structures complying with all applicable ordinances and statutes regulating buildings, electrical installations and plumbing and sanitation systems, and shall be located not closer than 10 feet nor farther than 200 feet from any trailer coach space.

(e) Each service building shall contain 2 slop sinks; one to be placed in the men's toilet and one in the women's toilet.

(f) The service buildings shall be well lighted at all times of the day or night, shall be well ventilated with screened openings, shall be constructed of such moisture-proof material, including painted woodwork, as shall permit repeated cleaning and washing, and shall be maintained at a temperature of at least 68 degrees Fahrenheit during the period from October 15th to May 1st. The floors of the service buildings shall be of water impervious material and shall slope to a floor drain connected with the sewage system.

(g) All service buildings and the grounds of the park shall be maintained in a clean, sightly condition and kept free of any condition that will menace the health of any occupant or the public or constitute a nuisance.

1342 (1222I). (Laundry Facilities.) The laundry facilities shall be provided in the ratio of one double laundry tub and ironing board for every 10 trailer coach spaces. An electric