

(c) Toilet facilities for men shall consist of not less than one flush toilet for every 15 trailer coach spaces, one shower or bath tub for every 10 trailer coach spaces, one lavatory for every 10 trailer coach spaces and one urinal for every 15 trailer coach spaces. Each toilet, shower and bath tub shall be in a private compartment.

(d) Service buildings housing the toilet facilities shall be permanent structures complying with all applicable ordinances and statutes regulating buildings, electrical installations and plumbing and sanitation systems, and shall be located not closer than 10 feet nor farther than 200 feet from any trailer coach space.

(e) Each service building shall contain 2 slop sinks; one to be placed in the men's toilet and one in the women's toilet.

(f) The service buildings shall be well lighted at all times of the day or night, shall be well ventilated with screened openings, shall be constructed of such moisture-proof material, including painted woodwork, as shall permit repeated cleaning and washing, and shall be maintained at a temperature of at least 68 degrees Fahrenheit during the period from October 15th to May 1st. The floors of the service buildings shall be of water impervious material and shall slope to a floor drain connected with the sewage system.

(g) All service buildings and the grounds of the park shall be maintained in a clean, sightly condition and kept free of any condition that will menace the health of any occupant or the public or constitute a nuisance.

305. (Laundry Facilities.) The laundry facilities shall be provided in the ratio of one double laundry tub and ironing board for every 10 trailer coach spaces. An electric outlet supplying current sufficient to operate an iron shall be located conveniently near the ironing board. Drying spaces shall be provided sufficient to accommodate the laundry of the trailer coach occupants. The service building housing the laundry facilities shall be a permanent structure complying with all applicable ordinances and statutes regulating buildings, electrical installations and plumbing and sanitation systems.

306. (Sewage and Refuse Disposal.) Waste from showers, bath tubs, toilets, slop sinks and laundries shall be discharged into a public sewer system in compliance with