

~~roads, schools, churches, public utilities and household services, use of adjacent territory for residential, agricultural or other purposes and maintenance of peace and good order, the Board of Health shall approve the application and upon completion of the park according to the plans shall issue the license.~~

Upon application for a transfer of the license, the Board of Health shall issue a transfer if the transferee is of good moral character.

751E. (Trailer Coach Park Plan.)

The trailer coach park shall conform to the following requirements:

(a) The park shall be located on a well-drained site, properly graded to insure rapid drainage and freedom from stagnant pools of water.

(b) Trailer coach spaces shall be provided consisting of a minimum of 1,000 square feet for each space which shall be at least 25 feet wide and clearly defined. Trailer coaches shall be so harbored on each space that there shall be at least a 15 foot clearance between trailer coaches, provided, however, that with respect to trailer coaches parked end-to-end, the end-to-end clearance between trailer coaches may be less than 15 feet but shall be not less than ten feet. No trailer coach shall be located closer than ten feet from any building within the park or from any property line bounding the park; PROVIDED, HOWEVER, THAT ANY TRAILER COACH PARK ALREADY IN OPERATION AT THE TIME OF THE ENACTMENT OF THIS SUBSECTION SHALL NOT BE REQUIRED TO CHANGE ITS EXISTING PARK PLAN IN ORDER TO COMPLY WITH THE PROVISIONS OF THIS SUB-SECTION.

(c) All trailer coach spaces shall abut upon a driveway of not less than 25 feet in width which shall have unobstructed access to a public street, alley or highway. All driveways shall be ~~hard surfaced~~ IMPROVED WITH GRAVEL OR SURFACING SO THAT THEY WILL NOT BE MUDDY, AND SHALL BE well marked in the daytime and lighted at night with 25 watt lamps at intervals of 100 feet located approximately 15 feet from the ground.

(d) Walkways not less than two feet wide shall be provided from the trailer coach spaces to the service buildings. The walkways shall be hard surfaced, well marked in the daytime and lighted at night with 25 watt lamps at inter-