

(f) *The service buildings shall be well lighted at all times of the day and night, shall be well ventilated with screened openings, shall be constructed of such moisture-proof material, including painted woodwork, as shall permit repeated cleaning and washing, and shall be maintained at a temperature of at least 68 degrees Fahrenheit during the period from October 1st to May 1st. The floors of the service buildings shall be of water impervious material.*

(g) *All service buildings and the grounds of the park shall be maintained in a clean, sightly condition and kept free of any condition that will menace the health of any occupant or the public or constitute a nuisance.*

217G. (Laundry Facilities.) *Laundry facilities shall be provided in the ratio of one double laundry tub for every 20 trailer coach spaces or one single laundry tub and one automatic or semi-automatic type washing machine for every 20 trailer coach spaces. An electrical outlet shall be provided supplying current sufficient to operate each washing machine. Drying spaces shall be provided sufficient to accommodate the laundry of the trailer coach occupants. The service building housing the laundry facilities shall be a permanent structure complying with all applicable ordinances and statutes regulating buildings, electrical installations and plumbing and sanitation systems.*

217H. (Sewage and Refuse Disposal.) *Waste from showers, bath tubs, flush toilets, urinals, lavatories, slop sinks and laundries in service and other buildings within the park shall be discharged into a public sewer system in compliance with applicable ordinances or into a private sewer and disposal plant or septic tank system of such construction and in such manner as will present no health hazard. Each trailer coach space shall be provided with a trapped sewer at least four inches in diameter, which shall be connected to receive the waste from the shower, bath tub, flush toilet, lavatory and kitchen sink of the trailer coach harbored in such space and having any or all of such facilities. The trapped sewer in each space shall be connected to discharge the trailer coach waste into a public sewer system in compliance with applicable ordinances or into a private sewer and disposal plant or septic tank system of such construction and in such manner as will present no health hazard.*

217-I. (Garbage Receptacles.) *Tightly covered metal garbage cans, OR OTHER SUITABLE GARBAGE RECEPTACLES, shall be provided for each trailer. The cans*