

(b) *Front and rear clearance lamps and identification lamps shall be capable of being seen and distinguished under normal atmospheric conditions at the times lights are required at all distances between 500 and 50 feet from the front and rear, respectively, of the vehicle.*

(c) *Side marker lamps shall be capable of being seen and distinguished under normal atmospheric conditions at the times lights are required at all distances between 500 and 50 feet from the side of the vehicle on which mounted.*

§ 12-212. *Obstructed lights not required.*

*Whenever motor and other vehicles are operated in combination during the time that lights are required, any lamp (except tail lamps) need not be lighted which, by reason of its location on a vehicle of the combination, would be obscured by another vehicle of the combination, but this shall not affect the requirement that lighted clearance lamps be displayed on the front of the foremost vehicle required to have clearance lamps, nor that all lights required on the rear of the rearmost vehicle of any combination shall be lighted.*

§ 12-213. *Lamps or flags on projecting load.*

(a) *Whenever the load upon any vehicle extends beyond the side or to the rear 4 feet or more beyond the bed or body of the vehicle there shall be displayed at the extreme rear end of the load, at the times specified in section 12-201, (1) two red lamps, visible from a distance of at least 500 feet to the rear, (2) two red reflectors meeting the requirements of section 12-211(a), visible from the rear and located so as to indicate maximum width, and (3) on each side one red lamp, visible from a distance of at least 500 feet to the side, located so as to indicate maximum overhang. There shall be displayed at all other times on any vehicle having a load which extends beyond either side more than 6 inches, or more than 4 feet beyond its rear, red flags, not less than 16 inches square, marking the extremities of such load, at each point a lamp is specified in the preceding sentence. Every such flag shall be so mounted or constructed that its full dimensions are visible at all times.*

(b) *This section in no way limits the provisions of section 14-103, or any other provision of law which prohibits certain extensions of loads on vehicles.*

§ 12-214. *Lamps on parked vehicles.*

(a) *Every vehicle shall be equipped with one or more lamps which, when lighted, display a white or amber light visible from a distance of 1,000 feet to the front of the vehicle, and a red light visible from a distance of 1,000 feet to the rear of the vehicle. The location of the lamp or lamps shall always be such that at least one lamp or combination of lamps meeting the requirements of this section is installed as near as practicable to the side of the vehicle which is closest to passing traffic. The foregoing provisions shall not apply to a motorcycle.*

(b) *Whenever a vehicle is parked or stopped upon a roadway, whether attended or unattended, when there is insufficient light to reveal any person or object within a distance of 100 feet upon the*