

dazzling light. Turn signal lamps may, but need not be, incorporated in other lamps on the vehicle.

§ 12-220. Omitted.

§ 12-221. *Additional lighting equipment.*

(a) Any motor vehicle may be equipped with not more than two side cowl or fender lamps which emit an amber or white light without glare, and which shall be located at or near the front of the vehicle.

(b) Any motor vehicle may be equipped with not more than one running-board courtesy lamp on each side thereof which emit a white or amber light without glare.

(c) Any motor vehicle may be equipped with one or more back-up lamps either separately or in combination with other lamps, but any such back-up lamp or lamps shall not be lighted when the motor vehicle is in forward motion.

(d) Any vehicle may be equipped with lamps which may be used for the purpose of warning the operators of other vehicles of the presence of a vehicular traffic hazard requiring the exercise of unusual care in approaching, overtaking or passing, and when so equipped may display the warning in addition to any other warning signals required by this article. The lamps used to display such warning to the front shall be mounted at the same level and as widely spaced laterally as practicable, and shall display simultaneously flashing white or amber lights, or any shade of color between white and amber. The lamps used to display the warning to the rear shall be mounted at the same level and as widely spaced laterally as practicable, and show simultaneously flashing amber or red lights, or any shade of color between amber and red. These warning lights shall be visible from a distance of not less than 1,500 feet under normal atmospheric conditions at night. Every motor vehicle registered in this State which was manufactured or assembled after June 30, 1967, and designated as a 1968 or subsequent year model shall be equipped either with these lamps or with some other device approved by the commissioner, by means of which the operator may cause both front and both rear turn signals to flash simultaneously as a vehicular traffic hazard warning.

(e) Any vehicle 80 inches or more in over-all width, if not otherwise required by Section 12-208, may be equipped with not more than three identification lamps showing to the front which emit an amber light without glare and not more than three identification lamps showing to the rear which emit a red light without glare. Such lamps shall be mounted as specified in subsection (b) of section 12-208.

§ 12-222. *Multiple-beam road-lighting equipment.*

(a) Except as hereinafter provided, the head lamps or the auxiliary driving lamp or combination thereof on motor vehicles other than motorcycles shall be so arranged that the driver may select at will between distributions of light projected to different elevations, and the lamps, in addition, may be so arranged that the selection can be made automatically, subject to the following limitations: