

(i) One, approximately 100 feet from the disabled vehicle in the center of the lane occupied by the vehicle and toward traffic approaching in that lane;

(ii) One, approximately 100 feet in the opposite direction from the disabled vehicle and in the center of the traffic lane occupied by the vehicle; and

(iii) One at the traffic side of the disabled vehicle not less than 10 feet rearward or forward thereof in the direction of the nearest approaching traffic. If a lighted red electric lantern or a red portable emergency reflector has been placed at the traffic side of the vehicle in accordance with paragraph (1) of this subsection, it may be used for this purpose.

(b) Whenever any vehicle of a type referred to in this section is disabled within 500 feet of a curve, hillcrest or other obstruction to view, the warning signal in that direction shall be placed to afford ample warning to other users of the highway, but in no case less than 100 feet or more than 500 feet from the disabled vehicle.

(c) Whenever any vehicle of a type referred to in this section is disabled upon any roadway of a divided highway during the time lights are required, the appropriate warning devices prescribed in subsections (a) and (e) of this section shall be placed as follows:

One at a distance of approximately 200 feet from the vehicle in the center of the lane occupied by the stopped vehicle and in the direction of traffic approaching in that lane; one at a distance of approximately 100 feet from the vehicle, in the center of the lane occupied by the vehicle and in the direction of traffic approaching in that lane; one at the traffic side of the vehicle and approximately 10 feet from the vehicle in the direction of the nearest approaching traffic.

(d) Whenever any vehicle of a type referred to in this section is disabled upon the traveled portion of a highway or the shoulder thereof outside of any municipality at any time the display of fusees, flares, red electric lanterns or portable red emergency reflectors is not required, the driver of the vehicle shall display two red flags upon the roadway in the lane of traffic occupied by the disabled vehicle, one at a distance of approximately 100 feet in advance of the vehicle, and one at a distance of approximately 100 feet to the rear of the vehicle.

(e) Whenever any motor vehicle used in the transportation of explosives or any cargo tank truck used for the transportation of any flammable liquid or compressed flammable gas, or any motor vehicle using compressed gas as a fuel, is disabled upon a highway of this State at any time or place mentioned in subsection (a) of this section, the driver of the vehicle shall immediately display the following warning devices: one red electric lantern or portable red emergency reflector placed on the roadway at the traffic side of the vehicle, and two red electric lanterns or portable red reflectors, one placed approximately 100 feet to the front and one placed approximately 100 feet to the rear of this disabled vehicle in the center of the traffic lane occupied by the vehicle. Flares, fusees, or signals produced by flame shall not be used as warning devices for disabled vehicles of the type mentioned in this subsection.

(f) The flares, fusees, red electric lanterns, portable red emergency reflectors, and flags to be displayed as required in this section