- (e) All disturbed areas of each such excavation shall be seeded or sodded as soon as the weather permits.
- (3) (a) Excavations OTHER THAN PROVIDED FOR IN SUBSECTION (2) OF THIS SECTION, AND which:
- (i) are less than four feet (4') in vertical depth at its deepest point as measured from the natural ground surface; and
- (ii) do not result in a total deposit of more than fifty (50) cubic yards of material on any lot, parcel or subdivision thereof; and
- (iii) do not impair existing surface drainage, constitute a potential erosion hazard, or act as a source of sedimentation to any adjacent land or watercourse; and
- (iv) have no final slopes more STEEP than one foot (1') vertical in three feet (3') horizontal TO ONE FOOT (1') VERTICAL; and
- (b) All disturbed areas of each such excavation shall be seeded or sodded as soon as weather permits.

(4) (a) A fill which:

- (i) is less than four feet (4') in vertical height at its deepest point as measured from the natural ground surface; and
- (ii) is placed on a surface having a slope not more than five feet (5') horizontal to one foot (1') vertical; and
- (iii) does not exceed a total of fifty (50) cubic yards of material on any lot, parcel or subdivision thereof; and
- (iv) does not impair existing surface drainage, constitute a potential erosion hazard or act as a source of sedimentation to any adjacent land or watercourse; and
- (v) has no final slopes more STEEP than one foot (1') vertical in three feet (3') horizontal TO ONE FOOT (1') VERTICAL; and further provided that
- (b) All disturbed areas of each such excavation shall be seeded or sodded as soon as the weather permits.
- (5) Accepted agricultural land management practices, including (but not limited to) plowing, nursery operations; the removal and/or transplanting of eultivated soil, shrubs, and trees; THE INSTALLATION OF CULTIVATED SOD; and tree cutting at or above existing ground, provided WHICH LEAVES the stump, ground cover and root mat remain intact.
- (6) The stockpiling of raw or processed sand, stone and gravel (with slopes at a natural angle of OF repose) at quarries, concrete, ASPHALT AND MATERIAL PROCESSING PLANTS AND STORAGE YARDS provided grading and sediment control measures have been utilized to protect against off-site damages, in accordance with the provisions of this Subtitle.