

ANNE ARUNDEL COUNTY

USE GROUP	CHARACTERISTICS OF THE BUILDING						
	Max. Height Above Grade	Max. Floor Area (Sq ft)	Types of Construction	Max. Exitway Access Travel Distance	Min. Fire Resistance of Exitway Enclosure	Min. Fire Resistance of Opening Protection	Max. Occupancy Load
L-2 (multi-family)	3 Stor-ies & attic	3000	1A, 1B 2A, 2E	50 ft.	2 Hour	3/4 Hour	6 Families 2 Families per floor
L-2 (multi-family)	3 Stor-ies & attic	2400	2C, 3A, 3B, 3C, 4A [[4B]]	50 ft.	2 Hour	3/4 Hour	6 Families 2 Families per floor
L-2 (multi-family)	2 Stor-ies & attic	3000	1A, 1E, 2A, 2B, 2C, 3A, 3B, 3C, 4A	50 ft.	1-1/2 Hour	3/4 Hour	4 Families per floor
E (Business)	3 Stor-ies	4000	1A, 1B, 2A	75 ft.	2 Hour	3/4 Hour	50
E (Business)	2 Stor-ies	3000	2E, 2C, 3A, 3B, 3C	75 ft.	2 Hour	3/4 Hour	50
E (Business)	2 Stor-ies	3000	4A, 4B	75 ft.	3/4 Hour	3/4 Hour	50 "