CHILDREN SHALL BE EQUIPPED WITH AN APPROVED FIRE ALARM SYSTEM."

(46) Strike all of Subsection 1219.14 and insert a new Subsection 1219.14 in lieu thereof, to stand in the place of the subsection so stricken, and to read as follows:

"SUBSECTION 1219.14. SCHOOL BUILDINGS: ALL SCHOOL BUILDINGS (USE GROUP F-4) WITH PROVISION FOR MORE THAN TEIRTY (30) CHILDREN SHALL BE EQUIPPED WITH AN APPROVED FIRE ALARM SYSTEM."

(47) Strike all of Subsection 1219.17 and insert a new Subsection 1219.17 in lieu thereof, to stand in the place of the subsection so stricken, and to read as follows:

"SUBSECTION 1219.17. BUSINESS BUILDINGS: ALL OFFICE BUILDINGS MORE THAN THREE (3) STORIES OR THIRTY FEFT (30') IN HEIGHT WITH AN OCCUPANCY LOAD OF MORE THAN FIFTY (50) PERSONS ABOVE THE FIRST FLOOR SHALL BE EQUIPPED WITH FITHER AN AUTOMATIC SPRINKLER SYSTEM OR AN APPROVED FIRE ALARM SYSTEM."

(48) Strike all of Subsection 1308.1 and insert a new Subsection 1308.1 in lieu thereof, to stand in the place of the subsection so stricken, and to read as follows:

"SUBSECTION 1308.1 TEMPORARY SUPPORT: THE PROVISIONS OF THIS SUBSECTION SHALL APPLY TO ALL EXCAVATIONS WHICH ARE FOUR FEET (4") OR MORE EFLOW THE EXISTING GRADE LEVEL. UNTIL PERMANENT SUPPORT HAS BEEN PROVIDED, ALL EXCAVATIONS SHALL BE SAFEGUARDED AND PROTECTED BY THE PERSON CAUSING THE EXCAVATIONS TO BE MADE, TO AVOID ALL DANGER TO LIFE OR LIMB. WHERE NECESSARY, SUCH EXCAVATIONS SHALL BE RETAINED BY TEMPORARY RETAINING WALLS, SHEET-PILING AND BRACING OR OTHER APPROVED METHOD TO SUPPORT THE ACJOINING EARTH. TEMPORARY SUPPORT NEED NOT BE PROVIDED IF THE SIDES OF THE EXCAVATION ARE SLOPED TO AN ANGLE OF FORTY-FIVE DEGREES (45°) OR MORE AWAY FROM VERTICAL."

(49) Strike all of Subsection 1308.21 and insert a new Subsection 1308.21 in lieu thereof, to stand in the place of the subsection so stricken, and to read as follows:

"SUBSECTION 1308.21. DEEP EXCAVATIONS: