

COUNTY LOCAL LAWS

804.1 PLASTIC PIPE SUPPORTS

HANGERS AND STRAPS SHALL NOT COMPRESS, DISTORT, CUT, OR UPGRADE THE PIPING AND SHALL ALLOW FREE MOVEMENT OF THE PIPE. PIPES SHALL BE SUPPORTED AT INTERVALS OF NOT MORE THAN FOUR FEET (4') AT END OF BRANCHES, AND AT CHANGE OF DIRECTION OR ELEVATION. SUPPORTS SHALL ALLOW FREE MOVEMENT. VERTICAL PIPING SHALL BE MAINTAINED IN STRAIGHT ALIGNMENT. TRAP ARMS IN EXCESS OF THREE FEET (3') SHALL BE SUPPORTED AS CLOSE AS POSSIBLE TO THE TRAP.

804.2 UNDERGROUND INSTALLATION

THE TRENCH BOTTOM SHALL BE SMOOTH AND OF UNIFORM GRADE, WITH EITHER UNDISTURBED GROUND OR A LAYER OF SELECTED AND COMPACTED BACKFILL SO THAT NO SETTLEMENT SHALL BE ENCOUNTERED. PIPE MUST BEAR ON THIS MATERIAL THROUGHOUT THE ENTIRE LENGTH OF ITS BURIAL."

(11) "SECTION 805 IN GROUND

PIPING IN THE GROUND SHALL BE LAID ON A FIRM BED FOR ITS ENTIRE LENGTH, EXCEPT WHERE SUPPORT IS OTHERWISE PROVIDED WHICH IS ADEQUATE IN THE JUDGMENT OF THE ADMINISTRATIVE AUTHORITY."

(12) "SECTION 901.1A INDIRECT WASTES REQUIRED

WASTES FROM THE FOLLOWING FIXTURES, DEVICES, APPLIANCES, OR APPARATUS SHALL DISCHARGE TO THE BUILDING DRAINAGE SYSTEM THROUGH INDIRECT WASTES, MEETING THE MATERIAL AND DRAINAGE PIPE SIZING REQUIREMENTS OF THIS CODE."

(13) "SECTION 1100.3 MINIMUM SIZE OF SOIL AND WASTED STACKS

NO SOIL OR WASTE STACK SHALL BE SMALLER THAN THE LARGEST HORIZONTAL BRANCH CONNECTED THERETO, EXCEPT THAT:

(A) A 4" X 3" WATER-CLOSET CONNECTION SHALL NOT BE CONSIDERED AS A REDUCTION IN PIPE SIZE.

(B) A FOUR INCH (4") HORIZONTAL DRAIN TO A THREE INCH (3") SOIL STACK BY MEANS OF A 3"