

REVISOR'S NOTE: This subsection presently appears as the second paragraph of Article 66C, section 486(d) of the Code. The only changes made are in style.

(M) "ENTRY" MEANS A PASSAGEWAY IN A COAL BED WHICH IS APPROXIMATELY LEVEL AND IS USED FOR HAULAGE, TRAVELING WAY, OR VENTILATION. IN A DIPPING BED, ENTRIES ON THE STRIKE ARE KNOWN AS "LEVELS" OR "GANGWAYS" AND TO THE DIP ARE KNOWN AS "SLOPES".

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 486 (e) of the Code. The only changes made are in style.

(N) "EXCAVATIONS AND WORKINGS" INCLUDES ANY EXCAVATED PORTION OF A MINE, WHETHER ABANDONED OR BEING WORKED. THE TERM ALSO INCLUDES ANY UNDERGROUND WORKINGS, SHAFTS, TUNNELS, AND OTHER WAYS AND OPENINGS INCLUDING THOSE BEING SUNK OR DRIVEN, TOGETHER WITH ROADS, APPLIANCES, MACHINERY, AND MATERIAL CONNECTED WITH THEM BELOW THE SURFACE.

REVISOR'S NOTE: This subsection presently appears as the first paragraph of Article 66C, section 486(f) of the Code. The only changes made are in style.

(O) "FACE" MEANS THE ADVANCING BREAST OF A MINE WORKING PLACE, EITHER OF AN ENTRY OR ROOM.

REVISOR'S NOTE: This subsection presently appears as Article 66C, the second paragraph of section 486(f) of the Code. The only changes made are in style.

(P) "GAS" IS USED IN THE SENSE ORDINARILY EMPLOYED BY MINERS, TO MEAN "FIRE DAMP", AND INFLAMMABLE GAS, CHIEFLY COMPOSED OF METHANE, SOMETIMES ACCOMPANIED BY ETHANE (C₂H₆) IN CASE OF LEAKAGE OF NATURAL GAS, AND EXPLOSIVE WHEN MIXED WITH AIR IN CERTAIN PROPORTIONS.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 486(g) of the Code. The only changes made are in style.

(Q) "GASSY MINE" MEANS A MINE OR PORTION OF A MINE IN WHICH METHANE IS FOUND BY AN APPROVED OR PERMISSIBLE FLAME SAFETY LAMP, DETECTOR, OR DEVICE, OR BY AIR ANALYSIS IN AN AMOUNT OF 0.25 PERCENT OR MORE.