

(G) CAR TO STOP BEFORE PERSONS LOAD OR UNLOAD; TO PROCEED IN ORDERLY MANNER.--A PERSON MAY NOT LOAD OR UNLOAD BEFORE THE CAR IN WHICH HE IS TO RIDE OR IS RIDING COMES TO A FULL STOP. HE SHALL PROCEED IN AN ORDERLY MANNER TO AND FROM ANY MAN TRIP.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 562(f) of the Code, as amended by Chapter 679, S.B. 390, Acts of 1973. The only changes made are in style.

(H) WAITING STATIONS.--A WAITING STATION SHALL BE PROVIDED WHERE ANY PERSON IS REQUIRED TO WAIT FOR ANY MAN TRIP OR MAN CAGE. IT SHALL HAVE SUFFICIENT ROOM, AMPLE CLEARANCE FROM MOVING EQUIPMENT, AND ADEQUATE SEATING FACILITIES. IF THERE IS A POSSIBILITY ANY PERSON MAY COME IN CONTACT WITH ENERGIZED ELECTRIC WIRING WHILE LOADING OR UNLOADING FROM A MAIN TRIP, TROLLEY AND POWER WIRES SHALL BE GUARDED EFFECTIVELY AT THE MAN TRIP STATIONS.

REVISOR'S NOTE: This subsection presently appears as the first paragraph of Article 66C, section 563 of the Code, as amended by Chapter 679, S.B. 390, Acts of 1973. The only changes made are in style.

(I) BELT LINES.--IF BELTS ARE USED TO TRANSPORT WORKERS, A MINIMUM CLEARANCE OF 18 INCHES SHALL BE MAINTAINED BETWEEN THE BELT AND THE ROOF OR CROSSBARS, PROJECTING EQUIPMENT, CAP PIECES, OVERHEAD CABLES, WIRING, AND OTHER OBJECTS. HOWEVER, WHERE THE HEIGHT OF THE COAL BED PERMITS, THE CLEARANCE MAY NOT BE LESS THAN 24 INCHES. THE BELT SPEED MAY NOT EXCEED 250 FEET PER MINUTE WHILE WORKERS ARE LOADING, UNLOADING, OR BEING TRANSPORTED. THE SPACE BETWEEN ANY TWO WORKERS RIDING ON A BELT LINE SHALL NOT BE LESS THAN FIVE FEET. LOADING AND UNLOADING STATIONS SHALL BE ILLUMINATED PROPERLY.

(J) SUPERVISION OF BELT AND MAN TRIPS.--AN OFFICIAL OR SOME OTHER PERSON DESIGNATED BY THE MINE FOREMAN SHALL SUPERVISE THE LOADING AND UNLOADING OF BELTS AND ANY MAN TRIP.

REVISOR'S NOTE: These subsections presently appear as the second through sixth paragraphs, inclusive, of Article 66C, section 563 of the Code, as amended by Chapter 679, S.B. 390, Acts of 1973. The