

RESISTORS.--RHEOSTATS, ELECTRIC HEATERS, AND RESISTORS SHALL BE LOCATED A SAFE DISTANCE FROM ANY COMBUSTIBLE MATERIAL.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 615(f) of the Code. The only changes made are in style.

(G) DE-ENERGIZING POWER WIRES.--WHERE PRACTICABLE UNDERGROUND POWER WIRES SHALL BE DE-ENERGIZED ON ANY IDLE DAY OR SHIFT.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 615(g) , of the Code. The only changes made are in style.

(H) ADOPTION OF PROCEDURES.--THE BUREAU SHALL ESTABLISH PROCEDURES TO BE FOLLOWED IF THERE IS A MINE FIRE OR EXPLOSION.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 615(i) of the Code. New language is added to this subsection to indicate that the bureau establishes the procedures. The only other changes made are in style.

7-448. STORAGE OF OIL AND GREASE.

A FIREPROOF UNDERGROUND STORAGE PLACE SHALL BE PROVIDED FOR OIL AND GREASE IN EXCESS OF TWO DAYS' SUPPLY. OIL AND GREASE KEPT IN A FACE REGION OR OTHER WORKING PLACE SHALL BE IN A PORTABLE, CLOSED, METAL CONTAINER.

REVISOR'S NOTE: This section is new language derived from the last sentence of Article 66C, section 615(d) of the Code.

7-449. MINE DISASTERS.

(A) NOTICE.--IF A MINE DISASTER OCCURS, THE PROPER STATE AND FEDERAL INSPECTION AUTHORITIES SHALL BE NOTIFIED PROMPTLY. ALL FACILITIES OF THE MINE SHALL BE MADE AVAILABLE FOR RECOVERY OPERATIONS.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 616(a) of the Code. The only changes made are in style.

(B) INSPECTION.--AFTER A DISASTER, WHEN THE MINE