

CONSTRUCTED OF TWO INCH HARDWOOD OR ITS EQUIVALENT. EACH METAL MAGAZINE SHALL BE LINED WITH NONSPARKING MATERIAL. NO MAGAZINE MAY BE PLACED IN A BUILDING CONTAINING OIL, GREASE, GASOLINE, WASTE PAPER, OR OTHER HIGHLY FLAMMABLE MATERIAL, NOR MAY IT BE PLACED LESS THAN 20 FEET FROM A STOVE, FURNACE, OPEN FIRE, OR FLAME.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 621(h) of the Code. The only changes made are in style.

(C) LOCATION.—IF FEASIBLE, THE LOCATION OF ANY MAGAZINE SHALL BE AT LEAST 200 FEET FROM ANY MINE OPENING UNLESS THE OPENING IS BARRICADED EFFECTIVELY.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 621(c) of the Code. The reference to "June 1, 1949" is proposed for deletion as obsolete. The only other changes made are in style.

(D) AMOUNT OF SUPPLY.—THE SUPPLY KEPT IN ANY DISTRIBUTING MAGAZINE SHALL BE LIMITED TO APPROXIMATELY ONE DAY'S REQUIREMENT. THE SUPPLY OF EXPLOSIVES AND DETONATORS MAY BE DISTRIBUTED FROM THE SAME MAGAZINE, IF SEPARATED BY AT LEAST A SIX INCH FASTENED HARDWOOD PARTITION OR ITS EQUIVALENT.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 621(d) of the Code. The only changes made are in style.

(E) AREA SURROUNDING MAGAZINE.—THE AREA WITHIN 25 FEET OF ANY MAGAZINE SHALL BE KEPT FREE OF RUBBISH, DRY GRASS, OR OTHER COMBUSTIBLE MATERIAL.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 621(e) of the Code. The only changes made are in style.

(F) LAMPS.—IF THE EXPLOSIVES MAGAZINE IS ILLUMINATED ELECTRICALLY, EACH LAMP SHALL BE OF AN EXPLOSION-PROOF TYPE, INSTALLED AND WIRED TO AFFORD MINIMUM FIRE AND CONTACT HAZARDS.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 621(f) of the Code. The only changes made are in style.

(G) NON METALLIC TOOLS; EXTRANEOUS