

RULE 5 - CARDOX MAY NOT BE SHOT OFF THE SOLID, OVER HEAVY ROCK BINDERS OR SHALE, OR IN A "TIGHT" SHOT.

RULE 6 - ANY CARDOX MISFIRE CAUSED BY THE FAILURE OF THE DISK TO RUPTURE MAY NOT BE APPROACHED UNTIL AFTER A WAITING PERIOD OF AT LEAST 15 MINUTES . A MINE FOREMAN OR HIS DESIGNEE SHALL SUPERVISE THE HANDLING OF THE MISFIRE. THE MISFIRED SHELL SHALL BE BLED OFF BEFORE REMOVAL FROM THE HOLE, AND MARKED CONSPICUOUSLY ON REMOVAL FROM THE HOLE.

REVISOR'S NOTE: This subsection presently appears as Article 66C, section 628 (a) and (b) of the Code. The only changes made are in style.

(P) AIRDOX.—WHERE AIRDOX IS USED FOR BLASTING OR BREAKING DOWN THE COAL, THE FOLLOWING RULES APPLY:

RULE 1 - COMPRESSED AIR SHALL BE CONDUCTED FROM THE COMPRESSOR TO WITHIN A PRACTICAL WORKING DISTANCE OF THE FACE BY A STEEL AIR LINE TESTED TO WITHSTAND AN APPROXIMATE PRESSURE OF 20,000 POUNDS PER SQUARE INCH.

RULE 2 - AIR LINES SHALL BE GROUNDED AT THE COMPRESSOR AND, IF POSSIBLE, AT OTHER LOW-RESISTANCE GROUND CONNECTIONS ALONG THE LINES, SUCH AS AT BORE-HOLE CASINGS. THEY MAY NOT BE CONNECTED IN ANY WAY TO ANY TRACK, WATER LINE, OR OTHER ELECTRIC POWER RETURN CONDUCTOR. THEY SHALL BE SUITABLY INSULATED WHERE THEY CROSS ELECTRIC WIRE OR UNDERNEATH THE TRACK.

RULE 3 - UNIONS SHALL BE INSTALLED IN EACH STEEL AIR LINE AT NOT MORE THAN 1,000 FOOT INTERVALS.

RULE 4 - A SHUTOFF VALVE SHALL BE INSTALLED EVERY 1,000 FEET IN ALL AIRDOX LINES AND BRANCH LINES AT A POINT NEAR THE MAIN LINES.

RULE 5 - AIRDOX LINES SHALL BE PROTECTED AT