(II) THE RED LIGHT EMITTED FROM THE TAIL LAMPS OF MOTOR VEHICLES (INCLUDING MOTORCYCLES) MANUFACTURED OR ASSEMBLED BEFORE THAT DATE NEED TO BE PLAINLY VISIBLE ONLY FROM A DISTANCE OF 300 FEET TO THE REAR.

(2) ON A COMBINATION OF VEHICLES, ONLY THE TAIL LAMPS ON THE REARMOST VEHICLE NEED ACTUALLY BE SEEN FROM THE DISTANCE SPECIFIED. ON VEHICLES EQUIPPED WITH MORE THAN ONE TAIL LAMP, THE LAMPS SHALL BE MOUNTED ON THE SAME LEVEL AND AS WIDELY SPACED LATERALLY AS PRACTICABLE.

(B) EVERY TAIL LAMP ON EVERY VEHICLE SHALL BE LOCATED AT A HEIGHT OF NCT MORE THAN 72 INCHES NOR LESS THAN 20 INCHES.

(C) EITHER A TAIL LAMP OR A SEPARATE LAMP SHALL BE CONSTRUCTED AND PLACED TC ILLUMINATE, WITH A WHITE LIGHT, THE REAR REGISTRATION PLATE AND RENDER IT CLEARLY LEGIBLE FROM A DISTANCE OF 50 FEET TO THE REAR. ANY TAIL LAMP OR TAIL LAMPS, TOGETHER WITH ANY SEPARATE LAMP OR LAMPS FOR ILLUMINATING THE REAR REGISTRATION PLATE, SHALL BE WIRED TO BE LIGHTED WHENEVER THE HEAD LAMPS OR AUXILIARY DRIVING LAMPS ARE LIGHTEC.

> REVISOR'S NOTE: This section presently appears as Art. 66 1/2, §12—204.
>
> Except for minimal changes in style and nomenclature, this section has not been revised; see General Revisor's Note to this title.

22—205.   REFLECTORS.

(A) (1) AFTER JULY 1, 1971, EVERY MOTOR VEHICLE, TRAILER, SEMITRAILER, AND POLE TRAILER SHALL CARRY ON THE REAR, EITHER AS PART OF THE TAIL LAMPS OR SEPARATELY, TWO OR MORE RED REFLECTORS MEETING THE REQUIREMENTS OF THIS SECTION, EXCEPT THAT:

(I) MOTORCYCLES SHALL CARRY AT LEAST ONE REFLECTOR; AND

(II) VEHICLES OF THE TYPES MENTIONED IN §22—208 OF THIS SUBTITLE SHALL BE EQUIPPED WITH REFLECTORS MEETING THE REQUIREMENTS OF §§22—210 AND 22—211(A) OF THIS SUBTITLE.

(2) BEFORE THIS DATE EVERY VEHICLE, TRAILER, OR SEMITRAILER, INCLUDING DEVICES MOVED BY MUSCULAR POWER, SHALL CARRY ON THE REAR AT LEAST ONE REFLECTOR, AND AFTER THIS DATE, EVERY VEHICLE MENTIONED IN THIS PARAGRAPH THAT IS NOT MENTIONED IN PARAGRAPH (1) OF THIS SUBSECTION SHALL CARRY ON THE REAR AT LEAST ONE REFLECTOR.