Annotated Code of Maryland (1977 Replacement Volume and 1978 Supplement)

Preamble

WHEREAS, The General Assembly finds that:

- 1. The Maryland Vehicle Law presently sets forth rules of the road with regard to the movement of pedestrians, in close conformity with the Uniform Vehicle Code; and
- 2. The Manual on Uniform Traffic Control Devices, the adopted State standard for the application and use of traffic control devices, contains several recommended designs for marking pedestrian crosswalks; and
- 3. Standards have not been adopted for use by State and local agencies responsible for crosswalk installations in the selection of crosswalk designs for various locations; and
- 4. A need exists for uniformity in the type of pedestrian crosswalks that are utilized at certain locations depending upon conditions; and
- 5. Legislative action is desirable to establish uniform criteria for pedestrian crosswalk markings and to direct the State Highway Administration and all affected agencies to review the pedestrian crosswalk problem in this State and develop a comprehensive program for its improvement; now, therefore,
- SECTION 1. BE IT ENACTED BY THE GENERAL ASSEMBLY OF MARYLAND, That section(s) of the Annotated Code of Maryland be repealed, amended, or enacted to read as follows:

Article - Transportation

21-101.

- (g-1) (1) "Marked crosswalk" means any part of a roadway that is distinctly indicated for pedestrian crossing by lines and markings as provided in [paragraph] PARAGRAPHS (2) AND (3) of this subsection.
- (2) [The] EXCEPT AS PROVIDED IN PARAGRAPH (3), THE markings indicating a marked crosswalk AT A TRAFFIC LIGHT, shall consist of two parallel solid white lines marking both edges of the crosswalk. These lines shall be at least six inches wide and at least six feet apart. However, in an area where the speed limit is more than 35 miles an hour, or where a crosswalk is located at other than an intersection, or where the existence of a crosswalk is unexpected, or where a crosswalk is located in a school zone, these lines [shall be at least] MAY BE INCREASED TO A