

WIDTH OF 24 inches [wide], and the space between them shall be hatched with diagonal white lines that are 12 to 24 inches wide and 12 to 24 inches apart.

(3) THE MARKINGS INDICATING A MARKED CROSSWALK AT AN INTERSECTION WITHOUT A TRAFFIC LIGHT SHALL CONSIST OF TWO PARALLEL SOLID WHITE LINES MARKING BOTH EDGES OF THE CROSSWALK. THESE LINES SHALL BE:

(I) 12 TO 24 INCHES WIDE, AND THE SPACE BETWEEN THEM SHALL BE HATCHED WITH DIAGONAL OR LONGITUDINAL WHITE LINES THAT ARE 12 TO 24 INCHES WIDE AND 12 TO 24 INCHES APART IN AN AREA WHERE:

- 1. THE SPEED LIMIT IS MORE THAN 35 MILES AN HOUR;
- 2. A CROSSWALK IS LOCATED AT OTHER THAN AN INTERSECTION;
- 3. THE EXISTENCE OF A CROSSWALK IS UNEXPECTED; OR
- 4. A CROSSWALK IS LOCATED IN A SCHOOL ZONE; AND

(II) AT LEAST 6 INCHES WIDE AND AT LEAST 6 FEET APART IN ALL OTHER AREAS.

25-104.

(A) The State Highway Administration shall adopt a manual and specifications for a uniform system of traffic control devices, consistent with the provisions of the Maryland Vehicle Law, for use on highways in this State. This uniform system shall correlate with and, as far as possible, conform to the system set forth in the most recent edition of the Manual on Uniform Traffic Control Devices for Streets and Highways.

(B) THE MANUAL AND SPECIFICATIONS ADOPTED BY THE ADMINISTRATION UNDER SUBSECTION (A) SHALL CONFORM TO THE SPECIFICATIONS OF SECTION 21-101 IN REGARD TO CROSSWALK MARKINGS AT INTERSECTIONS WITHOUT TRAFFIC LIGHTS.

SECTION 2. AND BE IT FURTHER ENACTED, That this Act shall take effect January 1, 1980.

Approved May 14, 1979.

-----

CHAPTER 402

(House Bill 1628)