

24-109.

[(a) (1) This subsection does not apply to any combination of vehicles while carrying international freight in a 20 foot semitrailer or container. However, this combination of vehicles is subject to the maximum load limits of axles set forth in § 24-108 of this subtitle and the maximum gross weight limits set forth in subsection (b) of this section.

(2) For purpose of this subsection, the distance between the first and last axles of a vehicle or combination of vehicles shall be measured horizontally between the centerlines of these axles.

(3) The gross weight of any vehicle or combination of vehicles may not exceed the following limits, prorated for fractions of a foot:

Distance between first and last axles (in feet)	Gross weight (in pounds)	Distance between first and last axles (in feet)	Gross weight (in pounds)
4	40,000	23	57,500
5	40,000	24	58,700
6	40,000	25	59,650
7	40,000	26	60,600
8	40,000	27	61,550
9	41,650	28	62,500
10	42,500	29	63,450
11	43,350	30	64,400
12	44,200	31	65,350
13	45,050	32	66,300
14	45,900	33	67,250
15	47,000	34	68,200
16	48,500	35	69,150
17	50,000	36	70,100
18	51,500	37	71,050
19	53,000	38	72,000
20	54,500	39	72,950
21	55,500	40	73,280
22	56,500		

Distance between first and last axles (in feet)	Maximum gross weight limit (in pounds) up to 5 axles	Maximum gross weight limit (in pounds) 6 axles
41	73,500	78,500
42	74,000	79,000
43	75,000	
44	75,500	