

(2) Is fastened securely to both the front and rear of the vehicle at both the front and rear of the load, as provided in this section.

(b) The fastening of a load to a vehicle shall be:

(1) By two separate common coil B.B. chains, the links of which may not be less than:

(i) 3/8th of an inch in diameter for loads of 3 tons or less; or

(ii) 1/2 of an inch in diameter for loads over 3 tons; or

(2) If they have at least as much tensile strength as the chains, by:

(i) Wire rope not less than 5/16th of an inch in diameter;

(ii) Steel strapping; [or]

(iii) Logistic webbing of synthetic fibers; OR

(3) AS SPECIFIED IN PART 393.102(B) (SECURITY SYSTEMS) OF THE FEDERAL MOTOR CARRIER SAFETY REGULATIONS.

(c) The chains and authorized alternative devices specified in this section:

(1) Shall be fastened with an adequate load binder of standard make or other appropriate fastening device; and

(2) May not be repaired or replaced by any links or material other than of the size, strength, and material specified in this section.

SECTION 2. AND BE IT FURTHER ENACTED, That this Act shall take effect July 1, 1983.

Approved May 10, 1983.

-----

CHAPTER 236

(House Bill 702)

AN ACT concerning

Board of Contract Appeals - Proceedings