

(a) Every reflector on any vehicle referred to in § 22-208 of this subtitle shall be of such size and characteristics and so maintained as to be readily visible at nighttime from all distances within 600 feet to 100 feet from the vehicle when directly in front of lawful upper beams of head lamps.

(B) Reflectors required to be mounted on the sides of the vehicle shall reflect the required color of light to the sides, and those mounted on the rear shall reflect a red color to the rear.

[(b)] (C) Front and rear clearance lamps and identification lamps shall be capable of being seen and distinguished under normal atmospheric conditions, at the times lights are required, at all distances between 500 and 50 feet from the front and rear, respectively, of the vehicle.

[(c)] (D) Side marker lamps shall be capable of being seen and distinguished under normal atmospheric conditions, at the times lights are required, at all distances between 500 and 50 feet from the side of the vehicle on which they are mounted.

22-213.

(a) Any vehicle carrying a load that extends beyond the side or to the rear 4 or more feet beyond the bed or body of the vehicle shall be equipped with the lamps and reflectors required by this section, in addition to other required lamps, at the times specified in § 22-201.1 of this subtitle.

(b) Loads projecting beyond sides of motor vehicles shall be marked as follows:

(1) The foremost edge of the projecting load, at its outermost extremity, shall be marked with an amber lamp visible from the front and side;

(2) The rearmost edge of the projecting load, at its outermost extremity, shall be marked with a red lamp visible from the rear and side;

(3) If any portion of the projecting load extends beyond both the foremost or rearmost edge, it shall be marked with an amber lamp visible from the front, side, and rear; or

(4) If the projecting load does not measure over 3 feet from front to rear, it shall be marked with an amber lamp visible from the front, side, and rear, except that, if the projection is located at or near the rear, it shall be marked by a red lamp visible from the front, side, and rear.

(c) Motor vehicles carrying loads that extend over 4 feet beyond the rear of the motor vehicle or that have tailboards or tailgates extending over 4 feet beyond the body shall have these projections marked: