

(1) On each side of the projecting load, by one red lamp, visible from the side and located so as to indicate maximum overhang; and

(2) On the rear of the projecting load, by two red lamps, visible from the rear, one at each side, and two red reflectors, visible from the rear, one at each side, located so as to indicate maximum width.

(d) On any vehicle with a load that extends beyond either side more than 6 inches or beyond its rear more than 4 feet there shall be displayed at all times, at each point a lamp is required, red flags, not less than 12 inches square, marking the extremities of the load.

(E) Every flag shall be so mounted or constructed that its full dimensions are visible at all times.

[(e)] (F) This section in no way expands the provisions of § 24-103 of this article, or any other provision of law that prohibits certain extensions of loads on vehicles.

[(f)] (G) This section does not apply to loads consisting of agricultural products, the nature of which would make installation of the required lights and reflectors impractical or unsafe.

22-218.1.

(a) Any rural letter carrier's motor vehicle may be equipped with a warning device for the purpose of warning the drivers of other vehicles of the presence of a vehicular traffic hazard requiring the exercise of unusual care in approaching, overtaking, and passing, and, when so equipped, may display the device in addition to any other warning signal required or permitted by law.

(b) The warning device shall include two bi-directional lights mounted at each side of the vehicle on the roof, with two amber lenses facing the rear and two amber lenses facing the front.

(C) Each light shall be at least 4 inches in diameter and shall be powered by a bulb of at least 21 candlepower, with reflectorization sufficient to assure visibility for at least 500 feet in front of and to the rear of the vehicle.

(D) The lights shall be wired with one "on-off" switch and one "flashing" switch, which shall activate both lights simultaneously, and which may be wired to operate from the vehicle's stoplight switch.

[(c)] (E) Between each light on the assembly of the device a sign shall be mounted with the words "U.S. Mail" in black