

letters on a white background, facing both to the front and the rear.

(F) The lettering on the sign shall be at least 4 inches in height, and the width of each stroke shall be at least $\frac{3}{4}$ of an inch.

(G) The sign shall be constructed to permit it to be folded down out of vision when not in use.

[[d]] (H) The warning device may be used only during the discharge of a rural letter carrier's official duties.

(I) Before the first stop on the route and following the last one the lights shall be darkened and the sign folded down out of vision.

[[e]] (J) The warning device may not be installed or operated until an application has been submitted to and approved by the Administration.

(K) The application shall be made by the individual rural letter carrier on forms furnished by the Administration.

22-219.

(a) Any vehicle may be equipped with and, when required under the Maryland Vehicle Law, shall be equipped with a stop lamp or lamps on the rear of the vehicle, which:

(1) Shall display a red or amber light, or any shade of color between red and amber, visible from a distance of not less than 300 feet to the rear in normal sunlight;

(2) Shall be actuated on application of the service (foot) brake; and

(3) May, but need not, be incorporated with one or more other rear lamps.

(b) [(1)] Any vehicle may be equipped with and, when required under § 22-206 (b) of this subtitle, shall be equipped with electric turn signals that indicate an intention to turn by flashing lights showing to the front and rear of a vehicle or on a combination of vehicles on the side of the vehicle or combination toward which the turn is to be made.

[(2)] (C) The lamps showing to the front shall be mounted on the same level and as widely spaced laterally as practicable and, when signaling, shall emit white or amber light, or any shade of light between white and amber.

(D) The lamps showing to the rear shall be mounted on the same level and as widely spaced laterally as practicable, and,