

handles, mirrors, tires, exhaust system, lights, glazing, windshield wipers, odometer, speedometer, bumpers, properly aligned wheels, wheels and wheel lugs, fenders, floor pans, hood, hood catches, [and] fuel system, FRONT SEAT, MOTOR MOUNTS, GEAR SELECTION INDICATOR FOR AUTOMATIC TRANSMISSIONS, UNIVERSAL JOINTS, AND SEAT BELTS OR COMBINATION SEAT BELT-SHOULDER HARNESS IF REQUIRED AS ORIGINAL EQUIPMENT UNDER SECTION 22-412 OR SECTION 22-412.1 OF THIS ARTICLE.

24-104.1.

(a) (1) In this section the following words have the meanings indicated.

(2) "Automobiles" means all [passenger type vehicles, including station wagons, minivans, sedans, panel and passenger vans, and pickup trucks certified as 3/4 ton or less by the manufacturer] ASSEMBLED MOTOR VEHICLES:

(I) CAPABLE OF BEING OPERATED ON A HIGHWAY; AND

(II) AUTHORIZED UNDER THIS ARTICLE TO BE OPERATED ON A HIGHWAY.

(3) "Saddle-mount and full-mount combinations" means a truck tractor or unloaded truck towing 1 or more other truck tractors or unloaded trucks in combination.

(4) MAXI-CUBE VEHICLE MEANS A NONARTICULATING STRAIGHT TRUCK, IN COMBINATION WITH A SEMITRAILER WHICH DOES NOT EXCEED 34 FEET, AND DESIGNED TO BE LOADED AND UNLOADED THROUGH THE SEMITRAILER.

(j) Except as otherwise provided in this section:

(1) In a combination of vehicles with a power unit that is a cargo carrying vehicle, the overall length of the combination may not exceed 55 feet;

(2) Any other combination of vehicles may not exceed 55 feet; and

(3) (i) A truck or truck tractor and semitrailer combination designed for and engaged exclusively in the transportation of automobiles, ~~MAXI-CUBE VEHICLES~~, or motorboats, MAXI-CUBE VEHICLES, and vehicles operating as saddle-mount and full-mount combinations may not exceed 65 feet in length.

(ii) No other length requirements may be applied to the combinations of vehicles described in item (i) of this paragraph.