

24-106.2.

(c) The fastening of a load to a vehicle shall be:

(1) By two separate common coil B.B. chains, the links of which may not be less than:

(i) [3/8th] 3/8 of an inch in diameter for loads of 3 tons or less; or

(ii) 1/2 of an inch in diameter for loads over 3 tons; or

(2) If they have at least as much tensile strength as the chains, by:

(i) Wire rope not less than [5/16th] 5/16 of an inch in diameter;

(ii) Steel strapping; OR

(iii) Logistic webbing of synthetic fibers; or

(3) As specified in Part 393.102(b) (securement systems) of the Federal Motor Carrier Safety Regulations.

DRAFTER'S NOTE:

Error: Stylistic errors and a conjunction omitted in § 24-106.2(c) of the Transportation Article.

Occurred: Stylistic errors occurred in Ch. 14, Acts of 1977. Conjunction omitted in Ch. 472, Acts of 1986. Correction of the omitted conjunction by Michie Company in the 1987 Replacement Volume of the Transportation Article is validated by this Act.

24-110.

(b) (1) The registration card for each vehicle specified in subsection (a) of this section[,] shall show the gross weight for which the vehicle is registered. If the registered vehicle is a motor vehicle to be used in combination with other vehicles, the registration card also shall show separately the total permissible gross weight of the combination of vehicles.

DRAFTER'S NOTE:

Error: Extraneous punctuation in § 24-110(b)(1) of the Transportation Article.

Occurred: Ch. 14, Acts of 1977.