

before June 1, 1971, shall have at least 1 tail lamp mounted on the rear [which] WHICH, when lighted as required in § 22-201.1 of this subtitle, shall emit a red light plainly visible from a distance of at least 300 feet to the rear.

## DRAFTER'S NOTE:

Error: Omitted comma in § 22-204(b) of the Transportation Article.

Occurred: Ch. 472, Acts of 1986.

22-213.

(d) On any vehicle with a load that extends beyond either side more than 6 inches or beyond its rear more than 4 feet there shall be displayed at all times, at each point a lamp is required, red or [orange-florescent] ORANGE-FLUORESCENT warning flags, not less than 18 inches square, marking the extremities of the load.

## DRAFTER'S NOTE:

Error: Misspelling in § 22-213(d) of the Transportation Article.

Occurred: Ch. 720, Acts of 1988.

22-224.1.

(b) The head lamp or head lamps on a motorcycle may be of the single-beam or multiple-beam type, but in either event shall comply with the following requirements and limitations:

(1) The head lamp or head lamps on a motorcycle shall be of sufficient intensity to reveal a person or a vehicle at a distance of:

(ii) Not less than 200 feet, when the motorcycle is operated at a speed of 25 TO 34 miles an hour [or more]; and

## DRAFTER'S NOTE:

Error: Inconsistent language in § 22-224.1(b) of the Transportation Article.

Occurred: Prior to the 1977 revision of the Transportation Article.

22-301.