

(2) That are constructed in accordance with the requirements of ANSI/ASHRAE Standard 15 (the safety code for mechanical refrigeration) in effect at the time of construction; and

(3) If none of the following limitations are exceeded:

- (i) A design pressure of 300 psig; or
- (ii) A design temperature of 210 degrees Fahrenheit.

(D) PIPES, PIPING COMPONENTS, AND THOSE STRUCTURES WHOSE PRIMARY FUNCTION IS THE TRANSPORT OF FLUIDS MAY NOT BE CONSIDERED PRESSURE VESSELS.

(E) SUBJECT TO THE PROVISIONS OF SUBSECTION (A)(7) OF THIS SECTION, WATER MAY CONTAIN ADDITIVES PROVIDED THE ASTM FLASH POINT OF THE AQUEOUS SOLUTION AT ATMOSPHERIC PRESSURE IS 185 DEGREES FAHRENHEIT OR HIGHER.

~~SECTION 2. AND BE IT FURTHER ENACTED, That this Act shall take effect October 1, 1994.~~

SECTION 2. AND BE IT FURTHER ENACTED, That this Act is an emergency measure, is necessary for the immediate preservation of the public health and safety, has been passed by a ye and nay vote supported by three-fifths of all the members elected to each of the two Houses of the General Assembly, and shall take effect from the date it is enacted.

Approved May 26, 1994.

---

**CHAPTER 702**

**(House Bill 1694)**

AN ACT concerning

**Transportation - BWI Airport - "Governor William Donald Schaefer International Terminal"**

FOR the purpose of naming the international terminal at Baltimore-Washington International Airport the "Governor William Donald Schaefer International Terminal".

BY adding to

Article - Transportation

Section 5-413(d)

Annotated Code of Maryland

(1993 Replacement Volume and 1993 Supplement)