

~~(11)~~ (10) "PASS-THROUGH CABINET" MEANS A COMMERCIAL REFRIGERATOR OR COMMERCIAL FREEZER WITH HINGED OR SLIDING DOORS ON BOTH THE FRONT AND REAR OF THE REFRIGERATOR OR FREEZER.

~~(12)~~ (11) (I) "REACH-IN CABINET" MEANS A COMMERCIAL REFRIGERATOR ~~OR~~ COMMERCIAL FREEZER, OR COMMERCIAL REFRIGERATOR-FREEZER WITH HINGED OR SLIDING DOORS OR LIDS, ~~BUT EXCLUDES~~.

(II) "REACH-IN CABINET" DOES NOT INCLUDE A ROLL-IN OR ROLL-THROUGH ~~CABINETS~~ CABINET ~~AND OR A PASS-THROUGH CABINETS~~ CABINET.

~~(13)~~ (12) "ROLL-IN CABINET" MEANS A COMMERCIAL REFRIGERATOR OR COMMERCIAL FREEZER WITH HINGED OR SLIDING DOORS THAT ~~ALLOWS~~ ALLOW WHEELED RACKS OF PRODUCT TO BE ROLLED INTO THE REFRIGERATOR OR FREEZER.

~~(14)~~ (13) "ROLL-THROUGH CABINET" MEANS A COMMERCIAL REFRIGERATOR OR COMMERCIAL FREEZER WITH HINGED OR SLIDING DOORS THAT ~~ALLOWS~~ ALLOW WHEELED RACKS OF PRODUCT TO BE ROLLED THROUGH THE REFRIGERATOR OR FREEZER.

~~(15)~~ "SET TOP BOX" ~~MEANS A DIGITAL CABLE TELEVISION BOX, WIRELESS TELEVISION RECEIVER, OR DIGITAL TELEVISION CONVERTER BOX.~~

~~(16)~~ (14) "TORCHIERE LIGHTING FIXTURE" MEANS A PORTABLE ELECTRIC LIGHTING FIXTURE WITH A REFLECTOR BOWL GIVING LIGHT DIRECTED UPWARD SO AS TO GIVE INDIRECT ILLUMINATION.

~~(17)~~ (15) "TRAFFIC SIGNAL" MEANS A DEVICE CONSISTING OF A SET OF SIGNAL LIGHTS OPERATING IN SEQUENCE AND PLACED AT INTERSECTIONS TO REGULATE TRAFFIC.

~~(18)~~ (16) "TRAFFIC SIGNAL MODULE" MEANS A STANDARD 8-INCH (200MM) OR 12-INCH (300MM) ROUND TRAFFIC SIGNAL INDICATION THAT:

(I) CONSISTS OF A LIGHT SOURCE; LENS, FULL-COLOR BALL, AND ALL PARTS NECESSARY FOR OPERATION; AND

(II) COMMUNICATES MOVEMENT MESSAGES TO DRIVERS THROUGH RED, AMBER, AND GREEN COLORS.

~~(19)~~ (17) "TRANSFORMER" MEANS A DEVICE CONSISTING ESSENTIALLY OF TWO OR MORE COILS OF INSULATED WIRE THAT TRANSFERS ALTERNATING CURRENT BY ELECTROMAGNETIC INDUCTION FROM ONE COIL TO ANOTHER IN ORDER TO CHANGE THE ORIGINAL VOLTAGE OR CURRENT VALUE.

~~(20)~~ (18) (I) "UNIT HEATER" MEANS A SELF-CONTAINED FAN-TYPE HEATER THAT:

1. IS DESIGNED TO BE INSTALLED WITHIN THE HEATED SPACE; AND