

(2) THE REGULATIONS SHALL PROVIDE FOR THE FOLLOWING MINIMUM EFFICIENCY STANDARDS:

(I) TORCHIERE FIXTURES MAY NOT CONSUME MORE THAN 190 WATTS AND MAY NOT BE CAPABLE OF OPERATING WITH LAMPS THAT TOTAL MORE THAN 190 WATTS;

(II) UNIT HEATERS MAY NOT HAVE PILOT LIGHTS AND SHALL HAVE EITHER POWER VENTING OR AN AUTOMATIC FLUE DAMPER;

(III) THE EFFICIENCY OF ALL LOW-VOLTAGE DRY-TYPE DISTRIBUTION TRANSFORMERS ~~SHALL BE NOT~~ MAY NOT BE LESS THAN THE VALUES SHOWN IN TABLE 4-2 OF NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION STANDARD TP-1-2002;

(IV) CEILING FANS AND CEILING FAN LIGHT KITS SHALL MEET THE TIER 1 CRITERIA OF VERSION 1.1 OF THE PRODUCT SPECIFICATION CONTAINED IN THE "ENERGY STAR PROGRAM REQUIREMENTS FOR RESIDENTIAL CEILING FANS", DEVELOPED BY THE U.S. ENVIRONMENTAL PROTECTION AGENCY ~~AND~~ THAT TOOK EFFECT ON JANUARY 1, 2002;

(V) RED AND GREEN TRAFFIC SIGNAL MODULES SHALL:

1. MEET THE REQUIREMENTS OF THE "ENERGY STAR PROGRAM REQUIREMENTS FOR TRAFFIC SIGNALS" DEVELOPED BY THE U.S. ENVIRONMENTAL PROTECTION AGENCY ~~AND~~ THAT TOOK EFFECT IN FEBRUARY 2001; AND

2. BE INSTALLED WITH COMPATIBLE, ELECTRICALLY-CONNECTED SIGNAL CONTROL INTERFACE DEVICES AND CONFLICT MONITORING SYSTEMS;

(VI) ILLUMINATED EXIT SIGNS SHALL MEET THE REQUIREMENTS OF THE "ENERGY STAR PROGRAM REQUIREMENTS FOR EXIT SIGNS" DEVELOPED BY THE U.S. ENVIRONMENTAL PROTECTION AGENCY ~~AND~~ THAT TOOK EFFECT ON JANUARY 1, 1999;

(VII) COMMERCIAL REFRIGERATION CABINETS SHALL MEET THE REQUIREMENTS SHOWN IN THE FOLLOWING TABLE IN WHICH "V" MEANS TOTAL VOLUME IN CUBIC FEET AND "AV" MEANS ADJUSTED VOLUME WHICH IS THE SUM OF THE VOLUME OF REFRIGERATED SPACE AND 1.63 TIMES THE VOLUME OF FREEZER SPACE:

EQUIPMENT TYPE	MAXIMUM DAILY ENERGY CONSUMPTION (KILOWATT HOURS)
REACH-IN CABINETS, PASS-THROUGH CABINETS, AND ROLL-IN OR ROLL-THROUGH CABINETS THAT ARE REFRIGERATORS WITH SOLID DOORS	0.125V + 2.76