In subsection (a)(3)(i)2 of this section, the reference to a building "used primarily" is substituted for the former reference to "devoted principally" for clarity.

In subsection (a)(3)(ii) of this section, the reference to a building "constructed of approved fire—resistant materials" is substituted for the former reference to a building "of an approved fire resistant construction" for clarity.

Also in subsection (a)(3)(ii) of this section, the reference to "shall be located at least" is substituted for the former reference to "may be no less than" for clarity and consistency within this section.

In subsection (a)(5) of this section, the reference to distances "prescribed" is substituted for the former reference to distances "specified or provided" for brevity and clarity.

In subsection (b)(1)(i) of this section, the reference to a fence that "is at least 6 feet tall" is substituted for the former reference to a fence "having a minimum height of six feet" for clarity.

In subsection (b)(1)(iii) of this section, the reference to gates being "kept securely locked when not in use" is substituted for the former reference to gates being locked "at all times, except when in actual use" for clarity.

In subsection (b)(2) of this section, the reference to "each building in a fireworks plant" is substituted for the former reference to "[a]ll buildings" for clarity.

In subsection (b)(3) of this section, the reference to an "unobstructed" view is substituted for the former reference to being in "plain" view for clarity.

Also in subsection (b)(3) of this section, the reference to "if the gate is" is substituted for the former reference to "while" for clarity.

In subsection (b)(4) of this section, the reference to "[t]he licensee" is added to clarify who has the obligation for seeing that conspicuous signs are posted.

Also in subsection (b)(4) of this section, the reference to signs "stat[ing]" is substituted for the former reference to signs "indicating" for clarity.

Also in subsection (b)(4) of this section, the reference to "at least every" 500 feet is substituted for the former reference to "at intervals not to exceed" 500 feet for brevity.

Defined terms: "Finishing and assembly building" § 10-101

"Fireworks" § 10-101

"Fireworks plant" § 10-101

"Mixing building" § 10-101