

(I) LIGHT IS PRODUCED BY THE PASSAGE OF AN ELECTRIC CURRENT THROUGH A VAPOR OR GAS;

(II) THE LIGHT-PRODUCING ARC IS STABILIZED BY BULB WALL TEMPERATURE; AND

(III) THE ARC TUBE HAS A BULB WALL LOADING IN EXCESS OF 3 WATTS PER SQUARE CENTIMETER.

[(6)] ~~(14)~~ (11) "Illuminated exit sign" means an internally illuminated sign that is designed to be permanently fixed in place to identify an exit and the background of which is not transparent.

[(7)] ~~(15)~~ (12) "Large packaged air-conditioning equipment" means packaged air-conditioning equipment with at least 20 tons but not more than 80 tons of cooling capacity.

[(8)] ~~(16)~~ (13) (i) "Low-voltage dry-type distribution transformer" means a distribution transformer that:

1. has an input voltage of 600 volts or less;
2. is air-cooled; and
3. does not use oil as a coolant.

(ii) "Low-voltage dry-type distribution transformer" does not include any of the following transformers:

1. an autotransformer in which the primary and secondary windings are not electronically isolated and at least a portion of the secondary voltage is derived from the primary winding;
2. a drive transformer designed only to provide power to operate an electronic variable speed motor drive;
3. a grounding transformer designed only to provide a system ground reference point;
4. a harmonic transformer designed to supply a load with a higher than normal harmonic current level and that has a k-rating of k-4 or greater;