cabinets, and roll-in or roll-through cabinets that are freezers with transparent doors

Reach—in cabinets that are 0.273AV + 1.65 refrigerator—freezers with solid doors

- (viii) large packaged air-conditioning equipment shall meet the Tier II requirements of the "Minimum Equipment Efficiencies for Unitary Commercial Air Conditioners" or "Minimum Equipment Efficiencies for Heat Pumps", as appropriate, developed by the Consortium for Energy Efficiency, Boston, Massachusetts, as in effect on January 1, 2002; and
- (ix) commercial clothes washers shall have a minimum modified energy factor of 1.26 and a maximum water consumption factor of 9.5, as measured in accordance with the federal test method for clothes washers as defined in 10 C.F.R. Section 430.23(j) (Appendix J1 to Subpart B of Part 430) (2001).
- (D) (1) ON OR BEFORE JANUARY 1, 2008, THE ADMINISTRATION SHALL ADOPT REGULATIONS ESTABLISHING MINIMUM EFFICIENCY STANDARDS FOR THE TYPES OF NEW PRODUCTS SET FORTH IN SUBSECTION (B)(1)(X) THROUGH (XVIII) (XVI) OF THIS SECTION.
- (2) THE REGULATIONS SHALL PROVIDE FOR THE FOLLOWING MINIMUM EFFICIENCY STANDARDS:
- (I) EXCEPT AS PROVIDED IN SUBSUBPARAGRAPH 2 OF THIS SUBPARAGRAPH:
- 1. BOTTLE-TYPE WATER DISPENSERS DESIGNED FOR DISPENSING BOTH HOT AND COLD WATER MAY NOT HAVE STANDBY ENERGY CONSUMPTION GREATER THAN 1.2 KILOWATT-HOURS PER DAY, AS MEASURED IN ACCORDANCE WITH THE TEST CRITERIA CONTAINED IN VERSION 1.1 OF THE U.S. ENVIRONMENTAL PROTECTION AGENCY'S "ENERGY STAR PROGRAM REQUIREMENTS FOR BOTTLED WATER COOLERS"; AND
- 2. BOTTLE-TYPE WATER DISPENSER UNITS WITH AN INTEGRAL, AUTOMATIC TIMER MAY NOT BE TESTED USING SECTION D, "TIMER USAGE" OF THE TEST CRITERIA;