

(II) COMMERCIAL HOT FOOD HOLDING CABINETS SHALL HAVE A MAXIMUM IDLE ENERGY RATE NOT EXCEEDING 40 WATTS PER CUBIC FOOT OF INTERIOR VOLUME, AS DETERMINED BY THE "IDLE ENERGY RATE-DRY TEST" IN ASTM F2140-01, "STANDARD TEST METHOD FOR PERFORMANCE OF HOT FOOD HOLDING CABINETS" PUBLISHED BY ASTM INTERNATIONAL, AND INTERIOR VOLUME SHALL BE MEASURED IN ACCORDANCE WITH THE METHOD SHOWN IN THE U.S. ENVIRONMENTAL PROTECTION AGENCY'S "ENERGY STAR PROGRAM REQUIREMENTS FOR COMMERCIAL HOT FOOD HOLDING CABINETS" EFFECTIVE AUGUST 15, 2003;

~~(III) COMPACT AUDIO PRODUCTS:~~

~~1. WITHOUT A PERMANENTLY ILLUMINATED CLOCK DISPLAY MAY NOT USE MORE THAN 2 WATTS IN STANDBY PASSIVE MODE;~~

~~2. WITH A PERMANENTLY ILLUMINATED CLOCK DISPLAY MAY NOT USE MORE THAN 4 WATTS IN STANDBY PASSIVE MODE; AND~~

~~3. SHALL BE MEASURED IN ACCORDANCE WITH INTERNATIONAL ELECTROTECHNICAL COMMISSION (IEC) TEST METHOD 62087:2002(E), "METHODS OF MEASUREMENT FOR THE POWER CONSUMPTION OF AUDIO, VIDEO, AND RELATED EQUIPMENT";~~

~~(IV) DIGITAL VERSATILE DISC PLAYERS AND DIGITAL VERSATILE DISC RECORDERS MAY NOT USE MORE THAN 3 WATTS IN STANDBY PASSIVE MODE, AS MEASURED IN ACCORDANCE WITH INTERNATIONAL ELECTROTECHNICAL COMMISSION (IEC) TEST METHOD 62087:2002(E), "METHODS OF MEASUREMENT FOR THE POWER CONSUMPTION OF AUDIO, VIDEO, AND RELATED EQUIPMENT";~~

~~(v) (III) METAL HALIDE LAMP FIXTURES DESIGNED TO BE OPERATED WITH LAMPS RATED AT LEAST 150 WATTS BUT NOT EXCEEDING 500 WATTS MAY NOT CONTAIN A PROBE-START METAL HALIDE BALLAST;~~

~~(vi) (IV) RESIDENTIAL FURNACES THAT USE NATURAL GAS OR PROPANE AND THAT ARE INSTALLED AS THE ORIGINAL FURNACE IN NEWLY CONSTRUCTED RESIDENTIAL BUILDINGS SHALL:~~

~~1. HAVE A MINIMUM ANNUAL FUEL UTILIZATION EFFICIENCY (AFUE) OF 90% AND A MAXIMUM ELECTRICITY RATIO OF 2%; AND~~

~~2. BE MEASURED IN ACCORDANCE WITH THE FEDERAL TEST METHOD FOR MEASURING THE ENERGY CONSUMPTION OF~~