

~~(2) STANDARD BULB RUNNING LIGHTS; OR~~

~~(3) LIGHT-EMITTING DIODE PODS AND STRIPS ADDED TO PROTECT THE DRIVER.~~

22-221.

(L) (1) SUBJECT TO PARAGRAPH (2) OF THIS SUBSECTION, A MOTORCYCLE MAY BE EQUIPPED WITH THE FOLLOWING AUXILIARY LIGHTING:

(I) BLUE DOT ILLUMINATION;

(II) STANDARD BULB RUNNING LIGHTS; OR

(III) LIGHT-EMITTING DIODE PODS AND STRIPS ADDED TO PROTECT THE DRIVER.

(2) (I) LIGHTING UNDER THIS SUBSECTION SHALL BE:

1. NONBLINKING;

2. NONFLASHING;

3. NONOSCILLATING; AND

4. DIRECTED TOWARD THE ENGINE AND THE DRIVE TRAIN OF THE MOTORCYCLE.

(II) LIGHTING UNDER THIS SUBSECTION MAY NOT:

1. BE ATTACHED TO THE WHEELS OF THE MOTORCYCLE; OR

2. EMIT A RED OR BLUE LIGHT.

(III) BLUE DOT ILLUMINATION:

1. MAY BE LOCATED ONLY ON THE REAR OF A MOTORCYCLE AS PART OF OR ADJACENT TO THE REAR BRAKE LIGHT; AND

2. MAY NOT EXCEED THREE-QUARTERS OF AN INCH IN DIAMETER.