

The Rest of the Said Story to be twenty four Inches thick upp to the first floor the walls of  
the second story of the said house porch and stairs case to be nineteene Inches thick upp to  
to the wall plate and soe from the wall plate to the crest of the windows of the Garret all  
the Gable ends and from the crest of the said window upp to the point of the Gable end —  
fourteen Inches thick onely the said porch to haue an arch in front six foot wide in the  
clear and eleven foot high to the Key stone of the Arch with two Arches on each side  
about the benches and agate into the hall of five foot wide and ten foot high the  
staircase to haue a door to open out of the hall of the same dimensions and a private  
door to open into the garden of three foot wide and six foot high vnder the first  
half pace of the stairs which stairs shall be half pace stairs six Inches and a  
half rising & a foot in stopp for the first story. and six Inches rising and a foot in  
stopp for the second story all to be made of good white Oke quartered plank and a window  
vppon each half pace the Inner doors of the first story of the said house to be four foot  
wide eight foot high as alsoe the windows of the Hall which shall be eight In number with  
double light divided with a transome att two thirds of the height of the said window the doors  
of the second story to be three foot & half wide and seven foot high and the windows of the  
said story two foot & half wide & five foot high with double light to be divided with a  
transome att two thirds of their height which said windows in the second story shall be eight  
in number as in the first story directly over the windows of the first story besides one in the  
second story in the porch of the same dimensions with those in the Chambers of the second  
story that there be three partitions in the second story as the Governour shall direct the said  
partitions double lathed and plaistred the floors to be laid with quartered plank inch &  
quarter thick after plaistred either good white Oke or Pine of this Countrey Sawen while  
the Turpentine is in them the doors all bolted with good Substantiall hinges Spring  
Stock Locks & Latches two Iron Casements to every window in the said house the frames  
and Casements to be well laid in Lynseed Oyle according to art and glazed with good  
Clear Square glasse the Summers and Girders for the floors to be sixteene & twelue Inches  
square the Iyes six and four Inches square standing twelue Inches a sunder the wall  
plates all round the house porch and stairs case to be twelue and seven Inches square  
the Rafters eighteene foot & half long standing twelue Inches a sunder with six pairs  
of principalls and double purlinders framed in even with the Rafters & to be mortised in every  
paire of Principalls to be braced in every paire of Rafters to haue two buttoned braces to  
the collar beams every paire of Principalls to be ten & eight Inches square the purlinders  
six Inches square the small Rafters four and three Inches square to be topped with  
mortice and Tennant and pinned att head & hepp tenanted att the foot the Laths for the  
tile of heart of white Oke & one Inch thick the principall Rafters of the porch & stairs case  
to be seven & five Inches & the foot of the Rafters to sett over a foot & half on each side  
with Plafboards att the Gable ends & Pivars over the whole house to be well plaistred within  
& the Roofer well sealed & the walls well pointed without with good lime the said Prison  
to be Substantiall built of Stone or brick laid in lime & sand twenty four foot long in the  
Clear